

G6AK-274P-ST40-US-DC5

G6AK-274P-ST40-US-DC5 Information



For Reference Only

Part Number G6AK-274P-ST40-US-DC5

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GENERAL PURPOSE DPDT 2A 5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6AK-274P-ST40-US-DC5 Specifications

Manufacturer Part NumberG6AK-274P-ST40-US-DC5ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysPackage-SeriesG6ARelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current72.5mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.5 VDC
Category Relays Signal Relays, Up to 2 Amps Package - Series G6A Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 72.5mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max
Package - Series G6A Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 72.5mA Coil Voltage SVDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage Signal Relays, Up to 2 Amps G6A Coid Coff General Purpose Latching, Dual Coil 72.5mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) 2A Switching Voltage 250VAC, 220VDC - Max
Package - G6A Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 72.5mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max
Series G6A Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 72.5mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max
Relay Type Coil Type Latching, Dual Coil Coil Current 72.5mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max
Coil Type Latching, Dual Coil Coil Current 72.5mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max
Coil Current 72.5mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max
Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max
Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max
Contact Rating (Current) Switching Voltage 2A 250VAC, 220VDC - Max
Switching Voltage 250VAC, 220VDC - Max
Turn On Voltage (Max) 3.5 VDC
Turn Off Voltage (Min) -
Operate Time 5ms
Release Time 5ms
Features -
Mounting Type Through Hole
Termination Style PC Pin
Report errors?

G6AK-274P-ST40-US-DC5 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6AK-274P-ST40-US-DC5 Payment Methods



















G6AK-274P-ST40-US-DC5 Shipping Methods













If you have any question about G6AK-274P-ST40-US-DC5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com