

G6AU-234P-ST-US-DC12

G6AU-234P-ST-US-DC12 Information



For Reference Only

Part Number G6AU-234P-ST-US-DC12

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE DPDT 1A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6AU-234P-ST-US-DC12 Specifications

Manufacturer Part NumberG6AU-234P-ST-US-DC12ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysBackage-SeriesG6ARelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current8.3mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5ms		
Category Relays Signal Relays, Up to 2 Amps Package - Series G6A Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 8.3mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Relays General Purpose General Purpose General Purpose Latching, Single Coil 1A 8.3mA 12VDC Contact Form DPDT (2 Form C) 1A Switching (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 5ms	Manufacturer Part Number	G6AU-234P-ST-US-DC12
Package - G6A Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 8.3mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 3250VAC, 220VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) - Operate Time 5ms	Manufacturer	Omron Electronics Inc-EMC Div
Package - G6A Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 8.3mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) - 5ms	Category	Relays
Series G6A Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 8.3mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) - Operate Time 5ms		Signal Relays, Up to 2 Amps
Relay Type Coil Type Latching, Single Coil Coil Current 8.3mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Seneral Purpose General Purpose Latching, Single Coil 8.3mA 12VDC 12VDC DPDT (2 Form C) 1A Switching Voltage 250VAC, 220VDC - Max 8.4 VDC Turn Off Voltage (Min) - Operate Time 5ms	Package	-
Coil Type Latching, Single Coil Coil Current 8.3mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) - Operate Time 5ms	Series	G6A
Coil Current 8.3mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 7urn Off Voltage (Min) Operate Time 5ms	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) - Operate Time 5ms	Coil Type	Latching, Single Coil
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 7urn Off Voltage (Min) Operate Time DPDT (2 Form C) 1A 250VAC, 220VDC - Max 8.4 VDC 5ms	Coil Current	8.3mA
Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) Operate Time 5ms	Coil Voltage	12VDC
Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) - Operate Time 5ms	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 8.4 VDC - 5ms	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time - 5ms	Switching Voltage	250VAC, 220VDC - Max
Operate Time 5ms	Turn On Voltage (Max)	8.4 VDC
	Turn Off Voltage (Min)	-
Release Time 5ms	Operate Time	5ms
	Release Time	5ms
Features -	Features	-
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

G6AU-234P-ST-US-DC12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6AU-234P-ST-US-DC12 Payment Methods



















G6AU-234P-ST-US-DC12 Shipping Methods













If you have any question about G6AU-234P-ST-US-DC12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com