

# **G6B-1174P-US-P6B DC6**

#### G6B-1174P-US-P6B DC6 Information



For Reference Only

Part Number G6B-1174P-US-P6B DC6

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GENERAL PURPOSE SPST 8A 6V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## G6B-1174P-US-P6B DC6 Specifications

Manufacturer Part Number  Manufacturer  Omron Electronics Inc-EMC Div  Relays  Power Relays, Over 2 Amps  Package  - Series  G6B  Relay Type  General Purpose  Coil Type  Non Latching  Coil Current  33.3mA  Coil Voltage  Contact Form  SPST-NO (1 Form A)  Contact Rating (Current)  8A  Switching Voltage  380VAC, 125VDC - Max  Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  10ms  Release Time  10ms  Features  Sealed - Fully, Socket Included  Mounting Type		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG6BRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage6VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.6 VDCOperate Time10msRelease Time10msFeaturesSealed - Fully, Socket Included	Manufacturer Part Number	G6B-1174P-US-P6B DC6
Package - Series G6B Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included	Manufacturer	Omron Electronics Inc-EMC Div
Package - G6B Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included	Category	Relays
SeriesG6BRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage6VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.6 VDCOperate Time10msRelease Time10msFeaturesSealed - Fully, Socket Included		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included	Package	-
Coil Type Non Latching Coil Current 33.3mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included	Series	G6B
Coil Current 33.3mA  Coil Voltage 6VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 8A  Switching Voltage 380VAC, 125VDC - Max  Turn On Voltage (Max) 4.2 VDC  Turn Off Voltage (Min) 0.6 VDC  Operate Time 10ms  Release Time 10ms  Features Sealed - Fully, Socket Included	Relay Type	General Purpose
Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 8A  Switching Voltage 380VAC, 125VDC - Max  Turn On Voltage (Max) 4.2 VDC  Turn Off Voltage (Min) 0.6 VDC  Operate Time 10ms  Release Time 10ms  Features Sealed - Fully, Socket Included	Coil Current	33.3mA
Contact Rating (Current)  Switching Voltage  380VAC, 125VDC - Max  Turn On Voltage (Max)  4.2 VDC  Turn Off Voltage (Min)  0.6 VDC  Operate Time  10ms  Release Time  10ms  Features  Sealed - Fully, Socket Included	Coil Voltage	6VDC
Switching Voltage 380VAC, 125VDC - Max  Turn On Voltage (Max) 4.2 VDC  Turn Off Voltage (Min) 0.6 VDC  Operate Time 10ms  Release Time 10ms  Features Sealed - Fully, Socket Included	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)  4.2 VDC  Turn Off Voltage (Min)  0.6 VDC  Operate Time  10ms  Release Time  10ms  Features  Sealed - Fully, Socket Included	Contact Rating (Current)	8A
Turn Off Voltage (Min)  Operate Time  10ms  Release Time  10ms  Features  Sealed - Fully, Socket Included	Switching Voltage	380VAC, 125VDC - Max
Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included	Turn On Voltage (Max)	4.2 VDC
Release Time 10ms Features Sealed - Fully, Socket Included	Turn Off Voltage (Min)	0.6 VDC
Features Sealed - Fully, Socket Included	Operate Time	10ms
·	Release Time	10ms
Mounting Type Through Hole	Features	Sealed - Fully, Socket Included
5	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

#### G6B-1174P-US-P6B DC6 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### G6B-1174P-US-P6B DC6 Payment Methods



















## G6B-1174P-US-P6B DC6 Shipping Methods













If you have any question about G6B-1174P-US-P6B DC6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com