

G6B-1174P-US-P6B DC6

G6B-1174P-US-P6B DC6 Information



For Reference Only

Part Number G6B-1174P-US-P6B DC6

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GENERAL PURPOSE SPST 8A 6V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6B-1174P-US-P6B DC6 Specifications

Manufacturer Part Number Manufacturer Omron Electronics Inc-EMC Div Relays Power Relays, Over 2 Amps Package - Series G6B Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included Mounting Type		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG6BRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage6VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.6 VDCOperate Time10msRelease Time10msFeaturesSealed - Fully, Socket Included	Manufacturer Part Number	G6B-1174P-US-P6B DC6
Package - Series G6B Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included	Manufacturer	Omron Electronics Inc-EMC Div
Package - G6B Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included	Category	Relays
SeriesG6BRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage6VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.6 VDCOperate Time10msRelease Time10msFeaturesSealed - Fully, Socket Included		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included	Package	-
Coil Type Non Latching Coil Current 33.3mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included	Series	G6B
Coil Current 33.3mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included	Relay Type	General Purpose
Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included	Coil Current	33.3mA
Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included	Coil Voltage	6VDC
Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included	Contact Rating (Current)	8A
Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included	Switching Voltage	380VAC, 125VDC - Max
Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included	Turn On Voltage (Max)	4.2 VDC
Release Time 10ms Features Sealed - Fully, Socket Included	Turn Off Voltage (Min)	0.6 VDC
Features Sealed - Fully, Socket Included	Operate Time	10ms
·	Release Time	10ms
Mounting Type Through Hole	Features	Sealed - Fully, Socket Included
5	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

G6B-1174P-US-P6B DC6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6B-1174P-US-P6B DC6 Payment Methods



















G6B-1174P-US-P6B DC6 Shipping Methods













If you have any question about G6B-1174P-US-P6B DC6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com