



G6B-2014P-US DC6 Information



For Reference Only

Part Number G6B-2014P-US DC6

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GENERAL PURPOSE DPST 5A 6V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6B-2014P-US DC6 Specifications

Manufacturer Part Number Manufacturer Category Relays Power Relays, Over 2 Amps Package - Series G6B Relay Type General Purpose Coil Type Non Latching Coil Current 50mA Coil Voltage Contact Form Contact Rating (Current) SA Switching Voltage Manufacturer G6B-2014P-US DC6 Omron Electronics Inc-EMC Div Relays Power Relays, Over 2 Amps - CofB General Purpose Non Latching Contact Form DPST (2 Form B) SA Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.8 VDC
Category Relays Power Relays, Over 2 Amps Package - Series G6B Relay Type General Purpose Coil Type Non Latching Coil Current 50mA Coil Voltage Contact Form DPST (2 Form B) Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max
Package - Series G6B Relay Type General Purpose Coil Type Non Latching Coil Current 50mA Coil Voltage 6VDC Contact Form DPST (2 Form B) Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max
Package - G6B Relay Type General Purpose Coil Type Non Latching Coil Current 50mA Coil Voltage 6VDC Contact Form DPST (2 Form B) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max
Series G6B Relay Type General Purpose Coil Type Non Latching Coil Current 50mA Coil Voltage 6VDC Contact Form DPST (2 Form B) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max
Relay Type General Purpose Coil Type Non Latching Coil Current 50mA Coil Voltage 6VDC Contact Form DPST (2 Form B) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max
Coil TypeNon LatchingCoil Current50mACoil Voltage6VDCContact FormDPST (2 Form B)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - Max
Coil Current50mACoil Voltage6VDCContact FormDPST (2 Form B)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - Max
Coil Voltage 6VDC Contact Form DPST (2 Form B) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max
Contact Form DPST (2 Form B) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max
Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max
Switching Voltage 380VAC, 125VDC - Max
Turn On Voltage (Max) 4.8 VDC
Turn Off Voltage (Min) 0.6 VDC
Operate Time 10ms
Release Time 10ms
Features Sealed - Fully
Mounting Type Through Hole
Termination Style PC Pin
Report errors?

G6B-2014P-US DC6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6B-2014P-US DC6 Payment Methods



















G6B-2014P-US DC6 Shipping Methods













If you have any question about G6B-2014P-US DC6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com