

G6BK-1114P-US-P6B DC6

G6BK-1114P-US-P6B DC6 Information



For Reference Only

Part Number G6BK-1114P-US-P6B DC6
Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GENERAL PURPOSE SPST 5A 6V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6BK-1114P-US-P6B DC6 Specifications

Manufacturer Part Number Manufacturer Omron Electronics Inc-EMC Div Relays Power Relays, Over 2 Amps Package Series G6B Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 46.8mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG6BRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current46.8mACoil Voltage6VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time10msFeaturesSealed - Fully, Socket IncludedMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G6BK-1114P-US-P6B DC6
Package - Series G6B Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 46.8mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included Mounting Type Termination Style PC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package - G6B Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 46.8mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesG6BRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current46.8mACoil Voltage6VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time10msFeaturesSealed - Fully, Socket IncludedMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type Coil Type Latching, Dual Coil Coil Current 46.8mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil Type	Series	G6B
Coil Current 46.8mA Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 6VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included Mounting Type Through Hole Termination Style PC Pin	Coil Type	Latching, Dual Coil
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included Mounting Type Through Hole Termination Style PC Pin	Coil Current	46.8mA
Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included Mounting Type Through Hole Termination Style PC Pin	Coil Voltage	6VDC
Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included Mounting Type Through Hole Termination Style 4.2 VDC	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	380VAC, 125VDC - Max
Operate Time 10ms Release Time 10ms Features Sealed - Fully, Socket Included Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	4.2 VDC
Release Time 10ms Features Sealed - Fully, Socket Included Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features Sealed - Fully, Socket Included Mounting Type Through Hole Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	10ms
Termination Style PC Pin	Features	Sealed - Fully, Socket Included
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

G6BK-1114P-US-P6B DC6 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6BK-1114P-US-P6B DC6 Payment Methods



















G6BK-1114P-US-P6B DC6 Shipping Methods













If you have any question about G6BK-1114P-US-P6B DC6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com