

Heisener.com

# **G6C-2117P-FD-US-DC24**

### G6C-2117P-FD-US-DC24 Information

Part Number G6C-2117P-FD-US-DC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE DPST 8A 24V

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **G6C-2117P-FD-US-DC24 Specifications**

Manufacturer Part Number       G6C-2117P-FD-US-DC24         Manufacturer       Omron Electronics Inc-EMC Div         Category       Relays         Power Relays, Over 2 Amps         Package       -         Series       G6C         Relay Type       General Purpose         Coil Type       Non Latching         Coil Current       8.3mA         Coil Voltage       24VDC         Contact Form       DPST-NO/NC (1 Form A and B)         Contact Rating (Current)       8A         Switching Voltage       380VAC, 125VDC - Max         Turn On Voltage (Max)       16.8 VDC         Turn Off Voltage (Min)       2.4 VDC         Operate Time       10ms         Release Time       10ms         Features       Sealed - Flux Protection         Mounting Type       Through Hole         Termination Style       PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG6CRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G6C-2117P-FD-US-DC24
Package - Series G6C Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Trmination Style PC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG6CRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesG6CRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose  Coil Type Non Latching  Coil Current 8.3mA  Coil Voltage 24VDC  Contact Form DPST-NO/NC (1 Form A and B)  Contact Rating (Current) 8A  Switching Voltage 380VAC, 125VDC - Max  Turn On Voltage (Max) 16.8 VDC  Turn Off Voltage (Min) 2.4 VDC  Operate Time 10ms  Release Time 10ms  Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Series	G6C
Coil Current Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPST-NO/NC (1 Form A and B)  Contact Rating (Current)  8A  Switching Voltage 380VAC, 125VDC - Max  Turn On Voltage (Max)  16.8 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time 10ms  Release Time 10ms  Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Coil Current	8.3mA
Contact Rating (Current)  Switching Voltage  380VAC, 125VDC - Max  Turn On Voltage (Max)  16.8 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  10ms  Release Time  10ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style	Coil Voltage	24VDC
Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPST-NO/NC (1 Form A and B)
Turn On Voltage (Max)  16.8 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  10ms  Release Time  10ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Contact Rating (Current)	8A
Turn Off Voltage (Min)  Operate Time  10ms  Release Time  10ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	380VAC, 125VDC - Max
Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	16.8 VDC
Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	2.4 VDC
Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	10ms
Termination Style PC Pin	Features	Sealed - Flux Protection
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

#### G6C-2117P-FD-US-DC24 Guarantees



## **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### G6C-2117P-FD-US-DC24 Payment Methods



















## **G6C-2117P-FD-US-DC24 Shipping Methods**













If you have any question about G6C-2117P-FD-US-DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com