



G6C-2117P-US-DC12 Information



For Reference Only

Part Number G6C-2117P-US-DC12

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPST 8A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6C-2117P-US-DC12 Specifications

Manufacturer Part Number G6C-2117P-US-DC12 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Package - Series G6C Relay Type General Purpose Coil Type Non Latching Coil Current 16.7mA Coil Voltage 12VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG6CRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current16.7mACoil Voltage12VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G6C-2117P-US-DC12
Package-SeriesG6CRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current16.7mACoil Voltage12VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG6CRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current16.7mACoil Voltage12VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesG6CRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current16.7mACoil Voltage12VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 16.7mA Coil Voltage 12VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current16.7mACoil Voltage12VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Series	G6C
Coil Current Coil Voltage 12VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 10ms Release Time 5eatures Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 7urn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style	Coil Current	16.7mA
Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style	Coil Voltage	12VDC
Switching Voltage Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style 380VAC, 125VDC - Max 8.4 VDC 1.2 VDC 10ms Formination Style Through Hole PC Pin	Contact Form	DPST-NO/NC (1 Form A and B)
Turn On Voltage (Max) Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style 8.4 VDC 1.2 VDC 10ms Formination Style 10ms Features PC Pin	Contact Rating (Current)	8A
Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	380VAC, 125VDC - Max
Operate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	8.4 VDC
Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1.2 VDC
Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	10ms
Termination Style PC Pin	Features	Sealed - Flux Protection
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

G6C-2117P-US-DC12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6C-2117P-US-DC12 Payment Methods



















G6C-2117P-US-DC12 Shipping Methods













If you have any question about G6C-2117P-US-DC12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com