



#### **G6C-2117P-US-DC24 Information**



For Reference Only

Part Number G6C-2117P-US-DC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE DPST 8A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **G6C-2117P-US-DC24 Specifications**

Manufacturer Part Number     G6C-2117P-US-DC24       Manufacturer     Omron Electronics Inc-EMC Div       Category     Relays       Power Relays, Over 2 Amps       Package     -       Series     G6C       Relay Type     General Purpose       Coil Type     Non Latching       Coil Current     8.3mA       Coil Voltage     24VDC       Contact Form     DPST-NO/NC (1 Form A and B)       Contact Rating (Current)     8A       Switching Voltage     380VAC, 125VDC - Max       Turn On Voltage (Max)     16.8 VDC       Turn Off Voltage (Min)     2.4 VDC       Operate Time     10ms       Release Time     10ms       Features     Sealed - Flux Protection       Mounting Type     Through Hole       Termination Style     PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG6CRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G6C-2117P-US-DC24
Package - Series G6C Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Trrmination Style PC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG6CRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesG6CRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose  Coil Type Non Latching  Coil Current 8.3mA  Coil Voltage 24VDC  Contact Form DPST-NO/NC (1 Form A and B)  Contact Rating (Current) 8A  Switching Voltage 380VAC, 125VDC - Max  Turn On Voltage (Max) 16.8 VDC  Turn Off Voltage (Min) 2.4 VDC  Operate Time 10ms  Release Time 10ms  Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Series	G6C
Coil Current Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms Release Time 5eatures Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPST-NO/NC (1 Form A and B)  Contact Rating (Current)  8A  Switching Voltage 380VAC, 125VDC - Max  Turn On Voltage (Max)  16.8 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  10ms  Release Time  10ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style	Coil Current	8.3mA
Contact Rating (Current)  Switching Voltage  380VAC, 125VDC - Max  16.8 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  10ms  Release Time  10ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style	Coil Voltage	24VDC
Switching Voltage  380VAC, 125VDC - Max  Turn On Voltage (Max)  16.8 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  10ms  Release Time  10ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Contact Form	DPST-NO/NC (1 Form A and B)
Turn On Voltage (Max)  16.8 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  10ms  Release Time  10ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Contact Rating (Current)	8A
Turn Off Voltage (Min)  Operate Time  10ms  Release Time  10ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	380VAC, 125VDC - Max
Operate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	16.8 VDC
Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	2.4 VDC
Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	10ms
Termination Style PC Pin	Features	Sealed - Flux Protection
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

#### **G6C-2117P-US-DC24 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **G6C-2117P-US-DC24 Payment Methods**



















### **G6C-2117P-US-DC24 Shipping Methods**













If you have any question about G6C-2117P-US-DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com