



G6C-2117P-US-DC6 Information

Heisener.com

Part Number G6C-2117P-US-DC6

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GENERAL PURPOSE DPST 8A 6V

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6C-2117P-US-DC6 Specifications

Manufacturer Part Number G6C-2117P-US-DC6 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Package - Series G6C Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 6VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG6CRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage6VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.6 VDCOperate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G6C-2117P-US-DC6
Package - GeC Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 6VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package - G6C Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 6VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesG6CRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage6VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.6 VDCOperate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 6VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil Type Non Latching Coil Current 33.3mA Coil Voltage 6VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Series	G6C
Coil Current 33.3mA Coil Voltage 6VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 6VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Current	33.3mA
Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max 4.2 VDC Turn Onf Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Voltage	6VDC
Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPST-NO/NC (1 Form A and B)
Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style 4.2 VDC	Contact Rating (Current)	8A
Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	380VAC, 125VDC - Max
Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	4.2 VDC
Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.6 VDC
Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	10ms
Termination Style PC Pin	Features	Sealed - Flux Protection
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
The post of the same of the sa		Report errors?

G6C-2117P-US-DC6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6C-2117P-US-DC6 Payment Methods



















G6C-2117P-US-DC6 Shipping Methods













If you have any question about G6C-2117P-US-DC6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com