

G6CK-1117P-US-DC5

G6CK-1117P-US-DC5 Information

Heisener.com

Part Number G6CK-1117P-US-DC5

Manufacturer Omron Electronics Inc-EMC Div

Category

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 10A 5V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6CK-1117P-US-DC5 Specifications

Manufacturer Part NumberG6CK-1117P-US-DC5ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG6CRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current56mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG6CRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current56mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G6CK-1117P-US-DC5
Package - GeC Series G6C Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 56mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Trinoul Series (Max) 15 VDC (Max) 15 V	Manufacturer	Omron Electronics Inc-EMC Div
Package - G6C Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 56mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesG6CRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current56mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 56mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil Type	Series	G6C
Coil Current Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Release Time 5eatures Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Latching, Dual Coil
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Current	56mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style	Coil Voltage	5VDC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style 3.5 VDC 3.5 VDC	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	250VAC, 125VDC - Max
Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	3.5 VDC
Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	10ms
Termination Style PC Pin	Features	Sealed - Flux Protection
·	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

G6CK-1117P-US-DC5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6CK-1117P-US-DC5 Payment Methods



















G6CK-1117P-US-DC5 Shipping Methods













If you have any question about G6CK-1117P-US-DC5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com