

G6CK-2117P-US-DC6 Information

Heisener.com

Part Number G6CK-2117P-US-DC6

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GENERAL PURPOSE DPST 8A 6V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6CK-2117P-US-DC6 Specifications

Manufacturer Part NumberG6CK-2117P-US-DC6ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysPackage-SeriesG6CRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current46.7mACoil Voltage6VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPackage-SeriesG6CRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current46.7mACoil Voltage6VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Manufacturer Part Number	G6CK-2117P-US-DC6
Package - G6C Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 46.7mA Coil Voltage 6VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Trupose G6C General Purpose G6C General Purpose General Purpose General Purpose General Purpose General Purpose G6C Seneral Purpose General Purpose Genera	Manufacturer	Omron Electronics Inc-EMC Div
Package - G6C Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 46.7mA Coil Voltage 6VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Trivous General Purpose General Purpose General Purpose General Purpose Sealed - Flux Protection Turn Off Voltage (Min) 10ms	Category	Relays
SeriesG6CRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current46.7mACoil Voltage6VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 46.7mA Coil Voltage 6VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Package	-
Coil Type Latching, Dual Coil Coil Current 46.7mA Coil Voltage 6VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Series	G6C
Coil Current 46.7mA Coil Voltage 6VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Relay Type	General Purpose
Coil Voltage 6VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Coil Type	Latching, Dual Coil
Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Coil Current	46.7mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Coil Voltage	6VDC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Contact Form	DPST-NO/NC (1 Form A and B)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Contact Rating (Current)	8A
Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Switching Voltage	250VAC, 125VDC - Max
Operate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Turn On Voltage (Max)	4.2 VDC
Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Turn Off Voltage (Min)	-
Features Sealed - Flux Protection Mounting Type Through Hole	Operate Time	10ms
Mounting Type Through Hole	Release Time	10ms
	Features	Sealed - Flux Protection
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

G6CK-2117P-US-DC6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6CK-2117P-US-DC6 Payment Methods



















G6CK-2117P-US-DC6 Shipping Methods













If you have any question about G6CK-2117P-US-DC6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com