



### **G6DS-1A-H DC24 Information**



For Reference Only

Part Number G6DS-1A-H DC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPST 5A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **G6DS-1A-H DC24 Specifications**

Manufacturer Part Number       G6DS-1A-H DC24         Manufacturer       Omron Electronics Inc-EMC Div         Category       Relays         Power Relays, Over 2 Amps         Package       -         Series       G6DS         Relay Type       General Purpose         Coil Type       Non Latching         Coil Current       5mA         Coil Voltage       24VDC         Contact Form       SPST-NO (1 Form A)         Contact Rating (Current)       5A         Switching Voltage       250VAC, 30VDC - Max         Turn On Voltage (Max)       16.8 VDC         Turn Off Voltage (Min)       1.2 VDC         Operate Time       10ms         Release Time       5ms         Features       Sealed - Fully         Mounting Type       Through Hole         Termination Style       PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG6DSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current5mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G6DS-1A-H DC24
Package-SeriesG6DSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current5mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package         -           Series         G6DS           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         5mA           Coil Voltage         24VDC           Contact Form         SPST-NO (1 Form A)           Contact Rating (Current)         5A           Switching Voltage         250VAC, 30VDC - Max           Turn On Voltage (Max)         16.8 VDC           Turn Off Voltage (Min)         1.2 VDC           Operate Time         10ms           Release Time         5ms           Features         Sealed - Fully           Mounting Type         Through Hole           Termination Style         PC Pin	Category	Relays
SeriesG6DSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current5mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose  Coil Type Non Latching  Coil Current 5mA  Coil Voltage 24VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 5A  Switching Voltage 250VAC, 30VDC - Max  Turn On Voltage (Max) 16.8 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 10ms  Release Time 5ms  Features Sealed - Fully  Mounting Type Through Hole  Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current5mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	G6DS
Coil Current5mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 5A  Switching Voltage 250VAC, 30VDC - Max  Turn On Voltage (Max) 16.8 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 10ms  Release Time 5ms  Features Sealed - Fully  Mounting Type Through Hole  Termination Style PC Pin	Coil Current	5mA
Contact Rating (Current)  Switching Voltage  250VAC, 30VDC - Max  Turn On Voltage (Max)  16.8 VDC  Turn Off Voltage (Min)  1.2 VDC  Operate Time  10ms  Release Time  5ms  Features  Sealed - Fully  Mounting Type  Through Hole  Termination Style	Coil Voltage	24VDC
Switching Voltage 250VAC, 30VDC - Max  Turn On Voltage (Max) 16.8 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 10ms  Release Time 5ms  Features Sealed - Fully  Mounting Type Through Hole  Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)  16.8 VDC  Turn Off Voltage (Min)  1.2 VDC  Operate Time  10ms  Release Time  5ms  Features  Sealed - Fully  Mounting Type  Through Hole  Termination Style  PC Pin	Contact Rating (Current)	5A
Turn Off Voltage (Min)  Operate Time  10ms  Release Time  5ms  Features  Sealed - Fully  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	250VAC, 30VDC - Max
Operate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	16.8 VDC
Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1.2 VDC
Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Sealed - Fully
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
•		Report errors?

#### **G6DS-1A-H DC24 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **G6DS-1A-H DC24 Payment Methods**



















## **G6DS-1A-H DC24 Shipping Methods**













If you have any question about G6DS-1A-H DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com