



G6E-134P-ST-US-DC6 Information



For Reference Only

Part Number G6E-134P-ST-US-DC6

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GENERAL PURPOSE SPDT 2A 6V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6E-134P-ST-US-DC6 Specifications

Manufacturer Part Number Manufacturer Category Relays Signal Relays, Up to 2 Amps Package - Series G6E Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage (G6E-134P-ST-US-DC6 Omron Electronics Inc-EMC Div Relays Signal Relays, Up to 2 Amps - G6E General Purpose Mon Latching 33.3mA 6VDC Contact Form SPDT (1 Form C) 2A Switching Voltage 250VAC, 220VDC - Max
Category Relays Signal Relays, Up to 2 Amps Package - Series G6E Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 2A
Package - Series G6E Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 2A
Package - Series G6E Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 2A
Series G6E Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 2A
Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 2A
Coil Type Non Latching Coil Current 33.3mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 2A
Coil Current 33.3mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 2A
Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 2A
Contact Form SPDT (1 Form C) Contact Rating (Current) 2A
Contact Rating (Current) 2A
Switching Voltage 250VAC 220VDC - Max
250 TIC, 220 TDC TILL
Turn On Voltage (Max) 4.2 VDC
Turn Off Voltage (Min) 0.6 VDC
Operate Time 5ms
Release Time 5ms
Features Sealed - Fully
Mounting Type Through Hole
Termination Style PC Pin
Report errors?

G6E-134P-ST-US-DC6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6E-134P-ST-US-DC6 Payment Methods



















G6E-134P-ST-US-DC6 Shipping Methods













If you have any question about G6E-134P-ST-US-DC6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com