

G6EK-134P-ST-US DC1.5

G6EK-134P-ST-US DC1.5 Information



For Reference Only

Part Number G6EK-134P-ST-US DC1.5

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE SPDT 2A 1.5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6EK-134P-ST-US DC1.5 Specifications

Manufacturer Part Number G6EK-134P-ST-US DC1.5 Manufacturer Omron Electronics Inc-EMC Div Category Relays Signal Relays, Up to 2 Amps Package - Series G6E Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 133.3mA Coil Voltage 1.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 1.05 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style Person and Part of the American Street Part		
CategoryRelaysPackage-SeriesG6ERelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current133.3mACoil Voltage1.5VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)1.05 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G6EK-134P-ST-US DC1.5
Package-SeriesG6ERelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current133.3mACoil Voltage1.5VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)1.05 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG6ERelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current133.3mACoil Voltage1.5VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)1.05 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesG6ERelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current133.3mACoil Voltage1.5VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)1.05 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 133.3mA Coil Voltage 1.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 1.05 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil Type Latching, Dual Coil Coil Current 133.3mA Coil Voltage 1.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 1.05 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Series	G6E
Coil Current 133.3mA Coil Voltage 1.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 1.05 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 1.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 1.05 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Latching, Dual Coil
Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 1.05 VDC Turn Off Voltage (Min) Operate Time 5ms Release Time 5ms Release Time Sealed - Fully Mounting Type Through Hole Termination Style	Coil Current	133.3mA
Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 1.05 VDC Turn Off Voltage (Min) Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style	Coil Voltage	1.5VDC
Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 1.05 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) 1.05 VDC Turn Off Voltage (Min) Operate Time Sms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style 1.05 VDC	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	250VAC, 220VDC - Max
Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	1.05 VDC
Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	5ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Sealed - Fully
•	Mounting Type	Through Hole
Domont owners?	Termination Style	PC Pin
Report errors?		Report errors?

G6EK-134P-ST-US DC1.5 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6EK-134P-ST-US DC1.5 Payment Methods



















G6EK-134P-ST-US DC1.5 Shipping Methods













If you have any question about G6EK-134P-ST-US DC1.5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com