

G6EK-134P-ST-US-DC9 Information



umber	G6EK-134P-ST-US-DC9		
acturer	Omron Electronics Inc-EMC Div		
ory	Relays Signal Relays, Up to 2 Amps		
ption	RELAY GENERAL PURPOSE SPDT 2A 9V		
ge	-		
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com		



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G6EK-134P-ST-US-DC9 Specifications

Manufacturer Part Number G6EK-134P-ST-US-DC9 Manufacturer Omron Electronics Inc-EMC Div Category Relays Signal Relays, Up to 2 Amps Package - Series G6E Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 22.2mA Coil Voltage 9VDC Cotact Form SPDT (1 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 6.3 VDC Turn Off Voltage (Min) - Operate Time Sms Release Time Sealed - Fully Mounting Type Through Hole Features Sealed - Fully		
RelaysRelays, Up to 2 AmpsPackage-SeriesG6ERelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current2.2 mACoil Actor9VDCContact FormSPDT (1 Form C)Contact Rating (Current)20VAC, 220VDC - MaxSwitching YoltageS0VAC, 220VDC - MaxTurn On Voltage (Max)6.3 VDCCorpare TimeSmsRelease TimeSmallFeaturesSeade - FullyMounting TypeThrough HoleFemination StyleCorpanCorpanScorp HoleStrein StyleScorp HoleStrein StyleCorp Hole<	Manufacturer Part Number	G6EK-134P-ST-US-DC9
Signal Relays, Up to 2 AmpsPackage-SeriesG6ERelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current2.2.mACold CurrentSPDT (1 Form C)Contact FormSPDT (1 Form C)Contact Rating (Current)2.50VAC, 220VDC - MaxSwitching Voltage6.3 VDCTurn On Voltage (Max)-Coperate TimeSmsRelease TimeSmsFeaturesSaled - FullyMounting TypeThrough HoleFermination StylePC Fun	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG6ERelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current22.2mACoil Voltage9VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)6.3 VDCTurn Off Voltage (Min)-Operate TimeSmsRelease TimeSaled - FullyFeaturesScaled - FullyMounting TypePC Pin	Category	Relays
SeriesG6ERelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current22.2mACoil Voltage9VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage550VAC, 220VDC - MaxTurn On Voltage (Max)-Operate Time5msRelease TimeSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Type2.2mACoil Voltage9VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)6.3 VDCTurn Off Voltage (Min)-Qerate Time5msRelease TimeSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeLatching, Dual CoilCoil Current22.2mACoil Voltage9VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)6.3 VDCTurn Off Voltage (Min)-Operate Time5msRelease TimeSealed - FullyFeaturesSealed - FullyMounting TypePC Pin	Series	G6E
Coil Current22.2mACoil Voltage9VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)6.3 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage9VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage50VAC, 220VDC - MaxTurn On Voltage (Max)6.3 VDCTurn Off Voltage (Min)-Operate Time5msRelease TimeSealed - FullyFeaturesSealed - FullyMounting TypeCP inTermination StyleCP in	Coil Type	Latching, Dual Coil
Contact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)6.3 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Coil Current	22.2mA
Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)6.3 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Coil Voltage	9VDC
Switching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)6.3 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)6.3 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Contact Rating (Current)	2A
Turn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Switching Voltage	250VAC, 220VDC - Max
Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	6.3 VDC
Release Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn Off Voltage (Min)	-
FeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Operate Time	5ms
Mounting TypeThrough HoleTermination StylePC Pin	Release Time	5ms
Termination Style PC Pin	Features	Sealed - Fully
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
Report circles.		Report errors?

G6EK-134P-ST-US-DC9 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

G6EK-134P-ST-US-DC9 Payment Methods



G6EK-134P-ST-US-DC9 Shipping Methods



If you have any question about G6EK-134P-ST-US-DC9, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com