

# G6EU-134P-ST-US-DC3

### **G6EU-134P-ST-US-DC3 Information**

Heisener.com	 G6EU-134P-ST-US-DC3 Omron Electronics Inc-EMC Div Relays Signal Relays, Up to 2 Amps RELAY GENERAL PURPOSE SPDT 2A 3V - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## G6EU-134P-ST-US-DC3 Specifications

Manufacturer Part Number GGEU-134P-ST-US-DC3   Manufacturer Omron Electronics Inc-EMC Div   Category Relays   Category Relays   Package -   Series GGE   Relay Type General Purpose   Coil Type Latching, Single Coil   Coil Current 66.7mA   Cold Voltage SYDC   Cotact Form SPDT (1 Form C)   Cotact Rating (Current) 24   Switching Voltage (Max) 2.1 VDC   Turn On Voltage (Max) 2.1 VDC   Queree Time Sms   Release Time Small   Features Saeled - Fully   Mounting Type Chrong Hole		
CategoryRelaysSignal Relays, Up to 2 AmpsPackage-SeriesG6ERelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current66.7mACold CurrentSVDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Yoltage250VAC, 220VDC - MaxTurn On Voltage (Max).1 VDCCurrent GurentSmsRelease TimeSmsFeaturesSealed - FullyMounting TypePC Pin	Manufacturer Part Number	G6EU-134P-ST-US-DC3
Signal Relays, Up to 2 AmpsPackage-SeriesG6ERelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current66.7mACold CurrentSVDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)-Operate Time5msRelease TimeSmsFeaturesSeadel - FullyMounting TypeThrough HoleFermination StylePC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG6ERelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current66.7mACoil Voltage3VDCContact FormSPDT (1 Form C)Contact Rating (Current)AASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)-Operate TimeSmsRelease TimeSnsFeaturesSealed - FullyMounting TypeCring HoleTermination StyleCPin	Category	Relays
SeriesG6ERelay TypeGeneral PurposeCoil TypeLaching, Single CoilCoil Type66.7mACoil Current66.7mACoil Voltage3VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)-Operate TimeSmsRelase TimeSmsFeaturesSaled - FullyMounting TypeCring HoleFernination StyleCP in		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Type66.7mACoil Voltage3VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage (Max)2.1 VDCTurn On Voltage (Max).Operate TimeSmsRelase TimeSmsFeaturesSeadel - FullyMounting TypeChang HoleTermination StyleCP in	Package	-
Coil TypeLatching, Single CoilCoil Ourent66.7mACoil Voltage3VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max).1 VDCTurn Onf Voltage (Max).1 VDCPreate TimeSmsRelease TimeSealed - FullyFeaturesSealed - FullyMounting TypeProgne MaxFermination StylePC Pin	Series	G6E
Coil Current66.7mACoil Voltage3VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max).1 VDCTurn Off Voltage (Min).Operate Time5msRelease TimeSealed - FullyFeaturesSealed - FullyMounting TypePC Pin	Relay Type	General Purpose
Coil Voltage3VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn Or Voltage (Max)2.1 VDCTurn Off Voltage (Min)-Operate Time5msRelease TimeSealed - FullyFeaturesSealed - FullyMounting TypePC PinTermination StylePC Pin	Coil Type	Latching, Single Coil
Contact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)2.1 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleFernination StylePC Pin	Coil Current	66.7mA
Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)2.1 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Coil Voltage	3VDC
Switching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)2.1 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)2.1 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Contact Rating (Current)	2A
Turn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Switching Voltage	250VAC, 220VDC - Max
Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	2.1 VDC
Release Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn Off Voltage (Min)	-
FeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Operate Time	5ms
Mounting TypeThrough HoleTermination StylePC Pin	Release Time	5ms
Termination Style PC Pin	Features	Sealed - Fully
•	Mounting Type	Through Hole
Report errors <sup>o</sup>	Termination Style	PC Pin
Report criters.		Report errors?

#### G6EU-134P-ST-US-DC3 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

#### G6EU-134P-ST-US-DC3 Payment Methods



## G6EU-134P-ST-US-DC3 Shipping Methods



If you have any question about G6EU-134P-ST-US-DC3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com