

Heisener.com

# G6EU-134PL-ST-US-DC24

### **G6EU-134PL-ST-US-DC24 Information**

Part Number G6EU-134PL-ST-US-DC24

Manufacturer Omron Electronics Inc-EMC Div

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY GEN PURPOSE SPDT 2A 24V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **G6EU-134PL-ST-US-DC24 Specifications**

Manufacturer Part Number  Manufacturer  Omron Electronics Inc-EMC Div  Relays  Signal Relays, Up to 2 Amps  Package  - Series  G6E  Relay Type  General Purpose  Coil Type  Latching, Single Coil  Coil Current  16.7 mA  Coil Voltage  24VDC  Contact Form  SPDT (1 Form C)  Contact Rating (Current)  2A  Switching Voltage  250VAC, 220VDC - Max  Turn On Voltage (Max)  Turn Off Voltage (Min)  - Operate Time  Sms  Release Time  5ms  Release Time  5ms  Features  Sealed - Fully  Mounting Type  Through Hole  PC Pin		
CategoryRelaysPackage-SeriesG6ERelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current16.7mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G6EU-134PL-ST-US-DC24
Package-SeriesG6ERelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current16.7mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG6ERelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current16.7mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesG6ERelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current16.7mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current16.7mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type	Series	G6E
Coil Current Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Coil Type	Latching, Single Coil
Contact Form SPDT (1 Form C)  Contact Rating (Current)  Switching Voltage  250VAC, 220VDC - Max  Turn On Voltage (Max)  16.8 VDC  Turn Off Voltage (Min)  Operate Time  5ms  Release Time  5ms  Release Time  Sealed - Fully  Mounting Type  Through Hole  Termination Style	Coil Current	16.7mA
Contact Rating (Current)  Switching Voltage  250VAC, 220VDC - Max  Turn On Voltage (Max)  16.8 VDC  Turn Off Voltage (Min)  Operate Time  5ms  Release Time  5ms  Features  Sealed - Fully  Mounting Type  Through Hole  Termination Style	Coil Voltage	24VDC
Switching Voltage 250VAC, 220VDC - Max  Turn On Voltage (Max) 16.8 VDC  Turn Off Voltage (Min) - Operate Time 5ms  Release Time 5ms  Features Sealed - Fully  Mounting Type Through Hole  Termination Style PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Sms  Release Time  Features  Sealed - Fully  Mounting Type  Through Hole  Termination Style  16.8 VDC	Contact Rating (Current)	2A
Turn Off Voltage (Min)  Operate Time  Sms  Release Time  Features  Sealed - Fully  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	250VAC, 220VDC - Max
Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	16.8 VDC
Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	5ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Sealed - Fully
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

#### **G6EU-134PL-ST-US-DC24 Guarantees**



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### G6EU-134PL-ST-US-DC24 Payment Methods



















### G6EU-134PL-ST-US-DC24 Shipping Methods













If you have any question about G6EU-134PL-ST-US-DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com