

Heisener.com

G6EU-134PL-ST-US-DC5

G6EU-134PL-ST-US-DC5 Information

Part Number G6EU-134PL-ST-US-DC5

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GENERAL PURPOSE SPDT 2A 5V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6EU-134PL-ST-US-DC5 Specifications

Manufacturer Part Number G6EU-134PL-ST-US-DC5 Manufacturer Omron Electronics Inc-EMC Div Category Relays Signal Relays, Up to 2 Amps Package - Series G6E Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 79.4mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-SeriesG6ERelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current79.4mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G6EU-134PL-ST-US-DC5
Package-SeriesG6ERelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current79.4mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG6ERelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current79.4mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesG6ERelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current79.4mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current79.4mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Latching, Single Coil Coil Current 79.4mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Series	G6E
Coil Current 79.4mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Coil Type	Latching, Single Coil
Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 5ms Release Time 5ms Release Time 5ms Reatures Sealed - Fully Mounting Type Through Hole Termination Style	Coil Current	79.4mA
Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style	Coil Voltage	5VDC
Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Sms Release Time Features Sealed - Fully Mounting Type Through Hole Termination Style 3.5 VDC 3.5 VDC Sms Fnot	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	250VAC, 220VDC - Max
Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	3.5 VDC
Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	5ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Sealed - Fully
•	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

G6EU-134PL-ST-US-DC5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6EU-134PL-ST-US-DC5 Payment Methods



















G6EU-134PL-ST-US-DC5 Shipping Methods













If you have any question about G6EU-134PL-ST-US-DC5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com