

G6H-2-100-DC24 Information

Heisener.com

Part Number G6H-2-100-DC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY TELECOM DPDT 1A 24V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6H-2-100-DC24 Specifications

Manufacturer Part Number Manufacturer Omron Electronics Inc-EMC Div Relays Signal Relays, Up to 2 Amps Package - Series G6H Relay Type Telecom Coil Type Non Latching Coil Current 8.3mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time 2ms Features Mounting Type Through Hole Termination Style Report errors?		
CategoryRelaysPackage-SeriesG6HRelay TypeTelecomCoil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time3msRelease Time2msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G6H-2-100-DC24
Package-SeriesG6HRelay TypeTelecomCoil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time3msRelease Time2msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package - Series G6H Relay Type Telecom Coil Type Non Latching Coil Current 8.3mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 2ms Features - Mounting Type Through Hole Termination Style PC Pin	Category	Relays
Series G6H Relay Type Telecom Coil Type Non Latching Coil Current 8.3mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 2ms Features - Mounting Type Through Hole Termination Style PC Pin		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time3msRelease Time2msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current 8.3mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 2ms Features - Mounting Type Through Hole Termination Style PC Pin	Series	G6H
Coil Current Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 2ms Features - Mounting Type Through Hole Termination Style 8.3mA 8.3mA 8.3mA 8.3mA 8.3mA 9.4mDC 9 Though Hole 9C Pin	Relay Type	Telecom
Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 2ms Features - Mounting Type Through Hole Termination Style PD Pin	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 2ms Features - Mounting Type Through Hole Termination Style	Coil Current	8.3mA
Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 2ms Features - Mounting Type Through Hole Termination Style	Coil Voltage	24VDC
Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 2ms Features - Mounting Type Through Hole Termination Style 125VAC, 110VDC - Max 18 VDC 2.4 VDC Through Hole PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 2ms Features - Mounting Type Through Hole Termination Style 18 VDC 2.4 VDC Through Hole PC Pin	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time 3ms Release Time 2ms Features - Mounting Type Through Hole Termination Style 2.4 VDC 3ms Through Hole PC Pin	Switching Voltage	125VAC, 110VDC - Max
Operate Time 3ms Release Time 2ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	18 VDC
Release Time 2ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	2.4 VDC
Features - Mounting Type Through Hole Termination Style PC Pin	Operate Time	3ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	2ms
Termination Style PC Pin	Features	-
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

G6H-2-100-DC24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6H-2-100-DC24 Payment Methods



















G6H-2-100-DC24 Shipping Methods













If you have any question about G6H-2-100-DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com