

G6H-2-F-DC9

a Quote

G6H-2-F-DC9 Information

Heisener.com Gedal tervos dato tere	Part Number	G6H-2-F-DC9	
	Manufacturer	Omron Electronics Inc-EMC Div	
	Category	Relays Signal Relays, Up to 2 Amps	
	Description	RELAY TELECOM DPDT 1A 9V	- S
	Package	-	
		For the pricing/inventory/lead time, please contact us	e a
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G6H-2-F-DC9 Specifications

Manufacturer Part NumberG6H-2-F-DC9ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysCategorySignal Relays, Up to 2 AmpsPackage-SeriesG6HRelay TypeTelecomCoil TypeNon LatchingCoil Current15.5mACotact FormPVDCCotact Asting (Current)ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Man)0.9 VDCOperate TimeSmsRelease TimeJmsFeatures-Mounting TypeGuiface MountGuiface MountSurface MountGuiface MountGuiface MountFeatures-Guiface MountGuiface MountSurface MountGuiface MountSurface MountGuiface MountSurface MountGuiface MountSurface MountGuiface MountSurface MountGuiface mountSurface mountSu		
CategoryRelaysPackage-Package-SeriesG6HRelay TypeTelecomCoil TypeNon LatchingCoil Current15.5mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Yoltage25VAC, 110VDC - MaxTurn On Voltage (Max)0.9 VDCOperate Time3msRelease Time-Features-Mounting TypeSurface MountFernination StyleSurface MountFernination StyleSurface Mount	Manufacturer Part Number	G6H-2-F-DC9
Signal Relays, Up to 2 AmpsPackage-SeriesG6HRelay TypeTelecomCoil TypeNon LatchingCoil Current15.5mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)6.75 VDCOperate Time3msRelease Time2msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG6HRelay TypeTelecomCoil TypeNon LatchingCoil Current15.5mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)6.75 VDCOperate Time3msRelease Time2msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Category	Relays
SeriesG6HRelay TypeTelecomCoil TypeNon LatchingCoil Current15.5mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)0.9 VDCOperate Time3msRelase Time2msFeatures-Mounting TypeSurface MountTermination StyleGull Wing		Signal Relays, Up to 2 Amps
Relay TypeTelecomRelay TypeKon LatchingCoil TypeNon LatchingCoil Current15.5mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)IASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)0.9 VDCOperate Time3msRelease Time2msFeatures-Mounting TypeGull WingTermination StyleGull Wing	Package	-
Coil TypeNon LatchingCoil Type15.5mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)6.75 VDCOperate Time0.9 VDCRelease Time2msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Series	G6H
Coil Current15.5mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)0.9 VDCOperate Time3msRelease Time2msFeatures-Mounting TypeGull WingTermination StyleGull Wing	Relay Type	Telecom
Coil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)IASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)0.9 VDCOperate Time3msRelease Time2msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Coil Type	Non Latching
Contact FormDPDT (2 Form C)Contact Rating (Current)IASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)0.9 VDCOperate Time3msRelease Time2msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Coil Current	15.5mA
Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)0.9 VDCOperate Time3msRelease Time2msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Coil Voltage	9VDC
Switching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)0.9 VDCOperate Time3msRelease Time2msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)0.9 VDCOperate Time3msRelease Time2msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Contact Rating (Current)	1A
Turn Off Voltage (Min)0.9 VDCOperate Time3msRelease Time2msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Switching Voltage	125VAC, 110VDC - Max
Operate Time3msRelease Time2msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Turn On Voltage (Max)	6.75 VDC
Release Time2msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Turn Off Voltage (Min)	0.9 VDC
Features-Mounting TypeSurface MountTermination StyleGull Wing	Operate Time	3ms
Mounting TypeSurface MountTermination StyleGull Wing	Release Time	2ms
Termination Style Gull Wing	Features	-
	Mounting Type	Surface Mount
Report errors?	Termination Style	Gull Wing
		Report errors?

G6H-2-F-DC9 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

G6H-2-F-DC9 Payment Methods



G6H-2-F-DC9 Shipping Methods



If you have any question about G6H-2-F-DC9, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com