



G6HK-2-100-DC3 Information

Heisener.com

Part Number G6HK-2-100-DC3

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY TELECOM DPDT 1A 3V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6HK-2-100-DC3 Specifications

Manufacturer Part NumberG6HK-2-100-DC3ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysPackage-SeriesG6HRelay TypeTelecomCoil TypeLatching, Dual CoilCoil Current66.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPackage-SeriesG6HRelay TypeTelecomCoil TypeLatching, Dual CoilCoil Current66.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeatures-Mounting TypeThrough Hole	Manufacturer Part Number	G6HK-2-100-DC3
Package-SeriesG6HRelay TypeTelecomCoil TypeLatching, Dual CoilCoil Current66.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeatures-Mounting TypeThrough Hole	Manufacturer	Omron Electronics Inc-EMC Div
Package - G6H Relay Type Telecom Coil Type Latching, Dual Coil Coil Current 66.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) - Operate Time 3ms Release Time 3ms Features - Mounting Type Through Hole	Category	Relays
SeriesG6HRelay TypeTelecomCoil TypeLatching, Dual CoilCoil Current66.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeatures-Mounting TypeThrough Hole		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeLatching, Dual CoilCoil Current66.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeatures-Mounting TypeThrough Hole	Package	-
Coil Type Latching, Dual Coil Coil Current 66.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) - Operate Time 3ms Release Time 3ms Release Time 3ms Features - Mounting Type Through Hole	Series	G6H
Coil Current 66.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) - Operate Time 3ms Release Time 3ms Release Time 3ms Features - Mounting Type Through Hole	Relay Type	Telecom
Coil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeatures-Mounting TypeThrough Hole	Coil Type	Latching, Dual Coil
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) Operate Time 3ms Release Time 3ms Features - Mounting Type Through Hole	Coil Current	66.7mA
Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 7urn Off Voltage (Min) Operate Time 3ms Release Time 3ms Features - Mounting Type Through Hole	Coil Voltage	3VDC
Switching Voltage Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time Sms Features Mounting Type 125VAC, 110VDC - Max 2.25 VDC	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Sms Release Time 3ms Features - Mounting Type Through Hole	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time 3ms Release Time 3ms Features - Mounting Type Through Hole	Switching Voltage	125VAC, 110VDC - Max
Operate Time 3ms Release Time 3ms Features - Mounting Type Through Hole	Turn On Voltage (Max)	2.25 VDC
Release Time 3ms Features - Mounting Type Through Hole	Turn Off Voltage (Min)	-
Features - Mounting Type Through Hole	Operate Time	3ms
Mounting Type Through Hole	Release Time	3ms
	Features	-
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

G6HK-2-100-DC3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6HK-2-100-DC3 Payment Methods



















G6HK-2-100-DC3 Shipping Methods













If you have any question about G6HK-2-100-DC3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com