



### **G6J-2FL-Y DC24 Information**



For Reference Only

Part Number G6J-2FL-Y DC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Signal Relays, Up to 2 Amps

**Description** RELAY TELECOM DPDT 1A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **G6J-2FL-Y DC24 Specifications**

Manufacturer Part Number  Manufacturer  Omron Electronics Inc-EMC Div  Relays  Signal Relays, Up to 2 Amps  Package  - Series  G6J-Y  Relay Type  Telecom  Coil Type  Non Latching  Coil Current  9.2mA  Coil Voltage  Contact Form  DPDT (2 Form C)  Contact Rating (Current)  1A  Switching Voltage  125VAC, 110VDC - Max  Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  3ms  Release Time  3ms  Release Time  Surface Mount  Termination Style  Gel-y  Relays  Signal Relays, Up to 2 Amps  1		
CategoryRelaysPackage-SeriesGGJ-YRelay TypeTelecomCoil TypeNon LatchingCoil Current9.2mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time3msRelease Time3msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Manufacturer Part Number	G6J-2FL-Y DC24
Package - G6J-Y Relay Type Telecom Coil Type Non Latching Coil Current 9,2mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms Features - Mounting Type Surface Mount Termination Style GIJ-Y	Manufacturer	Omron Electronics Inc-EMC Div
Package - G6J-Y Relay Type Telecom Coil Type Non Latching Coil Current 9.2mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms Features - Mounting Type Surface Mount Termination Style GIJW ing	Category	Relays
SeriesG6J-YRelay TypeTelecomCoil TypeNon LatchingCoil Current9.2mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time3msRelease Time3msFeatures-Mounting TypeSurface MountTermination StyleGull Wing		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeNon LatchingCoil Current9.2mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time3msRelease Time3msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Package	-
Coil TypeNon LatchingCoil Current9.2mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time3msRelease Time3msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Series	G6J-Y
Coil Current Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Relay Type	Telecom
Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  125VAC, 110VDC - Max  Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  3ms  Release Time  3ms  Features  -  Mounting Type  Surface Mount  Termination Style	Coil Current	9.2mA
Contact Rating (Current)  Switching Voltage  125VAC, 110VDC - Max  Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  3ms  Release Time  3ms  Features  - Mounting Type  Surface Mount  Termination Style	Coil Voltage	24VDC
Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  3ms  Release Time  3ms  Features  - Mounting Type  Surface Mount  Termination Style  Gull Wing	Contact Rating (Current)	1A
Turn Off Voltage (Min)  Operate Time  3ms  Release Time  3ms  Features  - Mounting Type  Surface Mount  Termination Style  Gull Wing	Switching Voltage	125VAC, 110VDC - Max
Operate Time 3ms  Release Time 3ms  Features -  Mounting Type Surface Mount  Termination Style Gull Wing	Turn On Voltage (Max)	18 VDC
Release Time 3ms  Features - Mounting Type Surface Mount Termination Style Gull Wing	Turn Off Voltage (Min)	2.4 VDC
Features - Mounting Type Surface Mount Termination Style Gull Wing	Operate Time	3ms
Mounting Type Surface Mount Termination Style Gull Wing	Release Time	3ms
Termination Style Gull Wing	Features	-
	Mounting Type	Surface Mount
Report errors?	Termination Style	Gull Wing
		Report errors?

#### **G6J-2FL-Y DC24 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **G6J-2FL-Y DC24 Payment Methods**



















## **G6J-2FL-Y DC24 Shipping Methods**













If you have any question about G6J-2FL-Y DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com