



G6K-2G-TR DC24 Information

www.helsener.com

For Reference Only

Part Number G6K-2G-TR DC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY TELECOM DPDT 1A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6K-2G-TR DC24 Specifications

Manufacturer Part Number G6K-2G-TR DC24 Manufacturer Omron Electronics Inc-EMC Div Category Relays Package - Series G6K Relay Type Telecom Coil Type Non Latching Coil Current 4.6mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms Features -		
CategoryRelays Signal Relays, Up to 2 AmpsPackage-SeriesG6KRelay TypeTelecomCoil TypeNon LatchingCoil Current4.6mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time3msRelease Time3ms	Manufacturer Part Number	G6K-2G-TR DC24
Package - Series G6K Relay Type Telecom Coil Type Non Latching Coil Current 4.6mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms	Manufacturer	Omron Electronics Inc-EMC Div
Package - Series G6K Relay Type Telecom Coil Type Non Latching Coil Current 4.6mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms	Category	Relays
SeriesG6KRelay TypeTelecomCoil TypeNon LatchingCoil Current4.6mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time3msRelease Time3ms		Signal Relays, Up to 2 Amps
Relay Type Telecom Coil Type Non Latching Coil Current 4.6mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms	Package	-
Coil TypeNon LatchingCoil Current4.6mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time3msRelease Time3ms	Series	G6K
Coil Current 4.6mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms	Relay Type	Telecom
Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms	Coil Current	4.6mA
Contact Rating (Current) Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms	Coil Voltage	24VDC
Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 3ms Release Time 3ms	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time Sms Release Time 3ms 3ms	Switching Voltage	125VAC, 60VDC - Max
Operate Time3msRelease Time3ms	Turn On Voltage (Max)	19.2 VDC
Release Time 3ms	Turn Off Voltage (Min)	2.4 VDC
	Operate Time	3ms
Features -	Release Time	3ms
	Features	-
Mounting Type Surface Mount	Mounting Type	Surface Mount
Termination Style J Lead	Termination Style	J Lead
Report errors?		Report errors?

G6K-2G-TR DC24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6K-2G-TR DC24 Payment Methods





















G6K-2G-TR DC24 Shipping Methods













If you have any question about G6K-2G-TR DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com