

G6K-2G-Y-TR DC5

G6K-2G-Y-TR DC5 Information

www.heisener.com	 G6K-2G-Y-TR DC5 Omron Electronics Inc-EMC Div Relays Signal Relays, Up to 2 Amps RELAY TELECOM DPDT 1A 5V - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G6K-2G-Y-TR DC5 Specifications

Manufacturer Part NumberG6K-2G-Y-TR DC5ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysPackageSignal Relays, Up to 2 AmpsPackage-SeriesG6KRelay TypeTelecomCoil TypeNon LatchingCoil Current21.1mACoil Actaing (Current)NDPDT (2 Form C)Contact FormDPDT (2 Form C)Contact Rating (Current)15VAC, 60VDC - MaxSwitching Voltage (Max)0.5 VDCTurn Of Voltage (Max)0.5 VDCQuerta Time3msRelease Time-Fatures-FaturesJurace MountFremination StyleJurace MountTurn On StyleSurface MountFatures-Mounting TypeJurace MountFatures-Fatures-Mounting TypeJurace MountTurn Or StyleSurface MountFatures-<		
CategoryRelaysPackage-Package-SeriesG6KRelay TypeTelecomCoil TypeNon LatchingCoil Current21.1mACoil OtageSVDCContact FormDPDT (2 Form C)Contact Ataing (Current)15VAC, 60VDC - MaxSwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)0.5 VDCContact Fine3msRelease Time-Features-Mounting TypeSuffice MountFemination StyleJLead	Manufacturer Part Number	G6K-2G-Y-TR DC5
Signal Relays, Up to 2 AmpsPackage-SeriesG6KRelay TypeTelecomCoil TypeNon LatchingCoil Current21.1mACoil VoltageSVDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)4 VDCOperate Time3msRelease Time3msFeatures-Mounting TypeSurface MountTentination StyleJ Lead	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG6KRelay TypeTelecomCoil TypeNon LatchingCoil Current21.1mACoil VoltageSVDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)4 VDCOperate Time3msRelease Time-Features-Mounting TypeSurface MountTermination StyleJ Lead	Category	Relays
SeriesG6KRelay TypeTelecomCoil TypeNon LatchingCoil Current21.1mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)IASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)0.5 VDCOperate Time3msRelease Time-Features-Mounting TypeSurface MountTermination StyleJLead		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeNon LatchingCoil Current21.1mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)0.5 VDCOperate Time3msRelease Time3msFeatures-Mounting TypeSurface MountTermination StyleJ Lead	Package	-
Coil TypeNon LatchingCoil TypeNon LatchingCoil Current21.1mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)4 VDCTurn Off Voltage (Max)0.5 VDCOperate Time3msRelease Time-Features-Mounting TypeSurface MountTermination StyleJ Lead	Series	G6K
Coil Current21.1mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)4 VDCTurn Off Voltage (Min)0.5 VDCOperate Time3msRelease Time-Features-Mounting TypeSurface MountTermination StyleJ Lead	Relay Type	Telecom
Coil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)IASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)4 VDCTurn Off Voltage (Min)0.5 VDCOperate Time3msRelease Time3msFeatures-Mounting TypeSurface MountTermination StyleJLead	Coil Type	Non Latching
Contact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)4 VDCTurn Off Voltage (Min)0.5 VDCOperate Time3msRelease Time3msFeatures-Mounting TypeSurface MountTermination StyleJ Lead	Coil Current	21.1mA
Contact Rating (Current)IASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)4 VDCTurn Off Voltage (Min)0.5 VDCOperate Time3msRelease Time3msFeatures-Mounting TypeSurface MountTermination StyleJ Lead	Coil Voltage	5VDC
Switching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)4 VDCTurn Off Voltage (Min)0.5 VDCOperate Time3msRelease Time3msFeatures-Mounting TypeSurface MountTermination StyleJ Lead	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)4 VDCTurn Off Voltage (Min)0.5 VDCOperate Time3msRelease Time3msFeatures-Mounting TypeSurface MountTermination StyleJ Lead	Contact Rating (Current)	1A
Turn Off Voltage (Min)0.5 VDCOperate Time3msRelease Time3msFeatures-Mounting TypeSurface MountTermination StyleJ Lead	Switching Voltage	125VAC, 60VDC - Max
Operate Time3msRelease Time3msFeatures-Mounting TypeSurface MountTermination StyleJ Lead	Turn On Voltage (Max)	4 VDC
Release Time3msFeatures-Mounting TypeSurface MountTermination StyleJ Lead	Turn Off Voltage (Min)	0.5 VDC
Features-Mounting TypeSurface MountTermination StyleJ Lead	Operate Time	3ms
Mounting TypeSurface MountTermination StyleJ Lead	Release Time	3ms
Termination Style J Lead	Features	-
-	Mounting Type	Surface Mount
Report errors?	Termination Style	J Lead
		Report errors?

G6K-2G-Y-TR DC5 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

G6K-2G-Y-TR DC5 Payment Methods



G6K-2G-Y-TR DC5 Shipping Methods



If you have any question about G6K-2G-Y-TR DC5, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com