

G6K-2P-Y DC3 Information



For Reference Only

Part Number G6K-2P-Y DC3

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY TELECOM DPDT 1A 3V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6K-2P-Y DC3 Specifications

Manufacturer Part Number G6K-2P-Y DC3 Manufacturer Omron Electronics Inc-EMC Div Category Relays Package - Series G6K Relay Type Telecom Coil Type Non Latching Coil Current 33mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 2.4 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 3ms Release Time 3ms Features - Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-SeriesG6KRelay TypeTelecomCoil TypeNon LatchingCoil Current33mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)2.4 VDCTurn Off Voltage (Min)0.3 VDCOperate Time3msRelease Time3msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G6K-2P-Y DC3
Package - Series G6K Relay Type Telecom Coil Type Non Latching Coil Current 33mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 2.4 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 3ms Release Time 3ms Features - Mounting Type Through Hole Termination Style PC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package - Series G6K Relay Type Telecom Coil Type Non Latching Coil Current 33mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 2.4 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 3ms Release Time 3ms Features - Mounting Type Through Hole Termination Style PC Pin	Category	Relays
Series G6K Relay Type Telecom Coil Type Non Latching Coil Current 33mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 2.4 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 3ms Release Time 3ms Features - Mounting Type Through Hole Termination Style PC Pin		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeNon LatchingCoil Current33mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)2.4 VDCTurn Off Voltage (Min)0.3 VDCOperate Time3msRelease Time3msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current33mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)2.4 VDCTurn Off Voltage (Min)0.3 VDCOperate Time3msRelease Time3msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Series	G6K
Coil Current 33mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 2.4 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 3ms Release Time 3ms Features Mounting Type Through Hole Termination Style PC Pin	Relay Type	Telecom
Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 2.4 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 3ms Release Time 3ms Release Time - 3ms Features - Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125 VAC, 60 VDC - Max Turn On Voltage (Max) 2.4 VDC Turn Off Voltage (Min) Operate Time 3ms Release Time 3ms Release Time - Mounting Type Through Hole Termination Style	Coil Current	33mA
Contact Rating (Current) Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 2.4 VDC Turn Off Voltage (Min) Operate Time 3ms Release Time 3ms Features - Mounting Type Through Hole Termination Style	Coil Voltage	3VDC
Switching Voltage Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time Sms Features - Mounting Type Through Hole Termination Style 125 VAC, 60 VDC - Max 2.4 VDC 0.3 VDC 3ms Through Hole PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Sims Release Time Features Mounting Type Through Hole Termination Style 2.4 VDC 3.3 VDC 3.3 SS 3.4 SS 4.5 SS 4	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time 3ms Release Time 3ms Features - Mounting Type Through Hole Termination Style 0.3 VDC 3ms Through Hole PC Pin	Switching Voltage	125VAC, 60VDC - Max
Operate Time 3ms Release Time 3ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	2.4 VDC
Release Time 3ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.3 VDC
Features - Mounting Type Through Hole PC Pin	Operate Time	3ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	3ms
Termination Style PC Pin	Features	-
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

G6K-2P-Y DC3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6K-2P-Y DC3 Payment Methods



















G6K-2P-Y DC3 Shipping Methods













If you have any question about G6K-2P-Y DC3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com