



G6KU-2F-RF DC24 Information



For Reference Only

Part Number G6KU-2F-RF DC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY RF DPDT 1A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6KU-2F-RF DC24 Specifications

Manufacturer Part Number G6KU-2F-RF DC24 Manufacturer Omron Electronics Inc-EMC Div Category Relays Signal Relays, Up to 2 Amps Package - Series G6K-RF Relay Type RF Coil Type Latching, Single Coil Coil Current 4.6mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 3ms Release Time 3ms Features 1 GHz Mounting Type Surface Mount Termination Style Gull Wing		
CategoryRelaysPackage-SeriesG6K-RFRelay TypeRFCoil TypeLatching, Single CoilCoil Current4.6mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeatures1 GHzMounting TypeSurface MountTermination StyleGull Wing	Manufacturer Part Number	G6KU-2F-RF DC24
Package-SeriesG6K-RFRelay TypeRFCoil TypeLatching, Single CoilCoil Current4.6mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeatures1 GHzMounting TypeSurface MountTermination StyleGull Wing	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG6K-RFRelay TypeRFCoil TypeLatching, Single CoilCoil Current4.6mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeatures1 GHzMounting TypeSurface MountTermination StyleGull Wing	Category	Relays
SeriesG6K-RFRelay TypeRFCoil TypeLatching, Single CoilCoil Current4.6mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeatures1 GHzMounting TypeSurface MountTermination StyleGull Wing		Signal Relays, Up to 2 Amps
Relay TypeRFCoil TypeLatching, Single CoilCoil Current4.6mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeatures1 GHzMounting TypeSurface MountTermination StyleGull Wing	Package	-
Coil Type Latching, Single Coil Coil Current 4.6mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 3ms Release Time 3ms Features 1 GHz Mounting Type Surface Mount Termination Style Guil Wing	Series	G6K-RF
Coil Current 4.6mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 3ms Release Time 3ms Features 1 GHz Mounting Type Surface Mount Termination Style Gull Wing	Relay Type	RF
Coil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeatures1 GHzMounting TypeSurface MountTermination StyleGull Wing	Coil Type	Latching, Single Coil
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) Operate Time 3ms Release Time 3ms Release Time 1 GHz Mounting Type Surface Mount Termination Style	Coil Current	4.6mA
Contact Rating (Current) Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) Operate Time 3ms Release Time 3ms Features 1 GHz Mounting Type Surface Mount Termination Style	Coil Voltage	24VDC
Switching Voltage Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time 3ms Release Time 3ms Features 1 GHz Mounting Type Surface Mount Termination Style	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Sms Release Time 3ms Features 1 GHz Mounting Type Surface Mount Termination Style	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time 3ms Release Time 3ms Features 1 GHz Mounting Type Surface Mount Termination Style Gull Wing	Switching Voltage	125VAC, 60VDC - Max
Operate Time3msRelease Time3msFeatures1 GHzMounting TypeSurface MountTermination StyleGull Wing	Turn On Voltage (Max)	18 VDC
Release Time 3ms Features 1 GHz Mounting Type Surface Mount Termination Style Gull Wing	Turn Off Voltage (Min)	-
Features 1 GHz Mounting Type Surface Mount Termination Style Gull Wing	Operate Time	3ms
Mounting Type Surface Mount Termination Style Gull Wing	Release Time	3ms
Termination Style Gull Wing	Features	1 GHz
	Mounting Type	Surface Mount
Papart arrors?	Termination Style	Gull Wing
Report errors:		Report errors?

G6KU-2F-RF DC24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6KU-2F-RF DC24 Payment Methods



















G6KU-2F-RF DC24 Shipping Methods













If you have any question about G6KU-2F-RF DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com