

G6KU-2F-RF-TR09DC4.5 Information

and the	All	 G6KU-2F-RF-TR09DC4.5 Omron Electronics Inc-EMC Div Relays Signal Relays, Up to 2 Amps RELAY RF DPDT 1A 4.5V - For the pricing/inventory/lead time, please contact	
F	or Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G6KU-2F-RF-TR09DC4.5 Specifications

Manufacturer Part Number G6KU-2F-RF-TR09DC4.5 Manufacturer Omron Electronics Inc-EMC Div Category Relays Signal Relays, Up to 2 Amps Signal Relays, Up to 2 Amps Package - Series G6K-RF Relay Type Ref Coil Type Latching, Single Coil Coil Current 23.2mA Coil Voltage 4.5VDC Cotact Form DPDT (2 Form C) Cotact Rating (Current) IA Switching Voltage (Max) 3.38 VDC Turn On Voltage (Max) - Operate Time Sms Release Time Sms Features I GHz Mounting Type Surface Mount		
CategoryRelaysCategoryRelaysPackage-Package-SeriesG6K-RFRelay TypeRFCoil TypeLatching, Single CoilCoil Current23.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Qerate TimeSinsRelease Time1GHzFatures1GHzMounting TypeSuiface MountTermination StyleGull Wing	Manufacturer Part Number	G6KU-2F-RF-TR09DC4.5
Signal Relays, Up to 2 AmpsPackage-SeriesG6K-RFRelay TypeRFCoil TypeLatching, Single CoilCoil Current23.2mACold Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)3.38 VDCCurnentSinsRelease TimeSmsRelease Time1 GHzFaturesSurface MountFurnination StyleSurface Mount	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG6K-RFRelay TypeRFCoil TypeLatching, Single CoilCoil Current23.2mACoil Otage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max).38 VDCQperate TimeSmsRelease TimeInsFeaturesIngMounting TypeSurface MountFermination StyleSurface MountFermination StyleSurface Mount	Category	Relays
SeriesG6K-RFRelay TypeRFCoil TypeLatching, Single CoilCoil Qurrent23.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate TimeSmsRelease Time1 GHzFeatures1 GHzMounting TypeGuil Wing		Signal Relays, Up to 2 Amps
Relay TypeRFCoil TypeLatching, Single CoilCoil Current23.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max).Operate Time3msRelease TimeInflyFeatures1GHzMounting TypeGuil WingTermination StyleGuil Wing	Package	-
Coil TypeLatching, Single CoilCoil Ourrent33.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time1GHzFatures1 GHzMounting TypeGuil Wing	Series	G6K-RF
Coil Current23.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeatures1 GHzMounting TypeSurface MountTermination StyleGull Wing	Relay Type	RF
Coil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time1 GHzFeatures1 GHzMounting TypeSurface MountFernination StyleGull Wing	Coil Type	Latching, Single Coil
Contact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeatures1 GHzMounting TypeSurface MountFernination StyleGull Wing	Coil Current	23.2mA
Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeatures1 GHzMounting TypeSurface MountFermination StyleGull Wing	Coil Voltage	4.5VDC
Switching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeatures1 GHzMounting TypeSurface MountTermination StyleGull Wing	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeatures1 GHzMounting TypeSurface MountTermination StyleGull Wing	Contact Rating (Current)	1A
Turn Off Voltage (Min)-Operate Time3msRelease Time3msFeatures1 GHzMounting TypeSurface MountTermination StyleGull Wing	Switching Voltage	125VAC, 60VDC - Max
Operate Time3msRelease Time3msFeatures1 GHzMounting TypeSurface MountTermination StyleGull Wing	Turn On Voltage (Max)	3.38 VDC
Release Time3msFeatures1 GHzMounting TypeSurface MountTermination StyleGull Wing	Turn Off Voltage (Min)	-
Features1 GHzMounting TypeSurface MountTermination StyleGull Wing	Operate Time	3ms
Mounting TypeSurface MountTermination StyleGull Wing	Release Time	3ms
Termination Style Gull Wing	Features	1 GHz
	Mounting Type	Surface Mount
Report errors?	Termination Style	Gull Wing
		Report errors?

G6KU-2F-RF-TR09DC4.5 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

G6KU-2F-RF-TR09DC4.5 Payment Methods



If you have any question about G6KU-2F-RF-TR09DC4.5, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com