

G6KU-2F-Y-TR DC4.5

G6KU-2F-Y-TR DC4.5 Information



For Reference Only

Part Number G6KU-2F-Y-TR DC4.5

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY TELECOM DPDT 1A 4.5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6KU-2F-Y-TR DC4.5 Specifications

Manufacturer Part Number Manufacturer Omron Electronics Inc-EMC Div Relays Signal Relays, Up to 2 Amps Package - Series G6K Relay Type Telecom Coil Type Latching, Single Coil Coil Current 23.2mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 3ms Release Time 3ms Features - Marking Time 3ms Features - Contact Manufacturer Amps Signal Relays Dept (2 Amps Apple (Amps) - Sms Sms Features - Contact Rating (Current) Sms Sms Features - Contact Rating (Current) Sms Sms		
CategoryRelaysPackage-SeriesG6KRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current23.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeatures-	Manufacturer Part Number	G6KU-2F-Y-TR DC4.5
Package - Series G6K Relay Type Telecom Coil Type Latching, Single Coil Coil Current 23.2mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) - Operate Time 3ms Release Time 3ms Features -	Manufacturer	Omron Electronics Inc-EMC Div
Package - Series G6K Relay Type Telecom Coil Type Latching, Single Coil Coil Current 23.2mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) - Operate Time 3ms Release Time 3ms Features -	Category	Relays
Series G6K Relay Type Telecom Coil Type Latching, Single Coil Coil Current 23.2mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) - Operate Time 3ms Release Time 3ms Features -		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeLatching, Single CoilCoil Current23.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3msFeatures-	Package	-
Coil Type Latching, Single Coil Coil Current 23.2mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) - Operate Time 3ms Release Time 3ms Features -	Series	G6K
Coil Current 23.2mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) - Operate Time 3ms Release Time 3ms Features -	Relay Type	Telecom
Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) - Operate Time 3ms Release Time 3ms Features -	Coil Type	Latching, Single Coil
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) Operate Time 3ms Release Time 3ms Features -	Coil Current	23.2mA
Contact Rating (Current) Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) Operate Time 3ms Release Time 3ms Features -	Coil Voltage	4.5VDC
Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) - Operate Time 3ms Release Time 3ms Features -	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time 3ms Features -	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time 3ms Release Time 3ms Features -	Switching Voltage	125VAC, 60VDC - Max
Operate Time 3ms Release Time 3ms Features -	Turn On Voltage (Max)	3.38 VDC
Release Time 3ms Features -	Turn Off Voltage (Min)	-
Features -	Operate Time	3ms
	Release Time	3ms
	Features	-
Mounting Type Surface Mount	Mounting Type	Surface Mount
Termination Style Gull Wing	Termination Style	Gull Wing
Report errors?		Report errors?

G6KU-2F-Y-TR DC4.5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6KU-2F-Y-TR DC4.5 Payment Methods



















G6KU-2F-Y-TR DC4.5 Shipping Methods













If you have any question about G6KU-2F-Y-TR DC4.5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com