



G6KU-2P-Y DC3 Information



For Reference Only

Part Number G6KU-2P-Y DC3

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY TELECOM DPDT 1A 3V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6KU-2P-Y DC3 Specifications

Manufacturer Part Number Manufacturer Omron Electronics Inc-EMC Div Relays Signal Relays, Up to 2 Amps Package - Series G6K Relay Type Telecom Coil Type Latching, Single Coil Coil Current 33mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 3ms Release Time 3ms		
Category Relays Signal Relays, Up to 2 Amps Package - Series G6K Relay Type Telecom Coil Type Latching, Single Coil Coil Current 33mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 3ms Release Time Relasse Time	Manufacturer Part Number	G6KU-2P-Y DC3
Package - Series G6K Relay Type Telecom Coil Type Latching, Single Coil Coil Current 33mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) - Operate Time 3ms Release Time 3ms	Manufacturer	Omron Electronics Inc-EMC Div
Package - G6K Relay Type Telecom Coil Type Latching, Single Coil Coil Current 33mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) - Operate Time 3ms Release Time 3ms	Category	Relays
Series G6K Relay Type Telecom Coil Type Latching, Single Coil Coil Current 33mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) - Operate Time 3ms Release Time 3ms		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeLatching, Single CoilCoil Current33mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)-Operate Time3msRelease Time3ms	Package	-
Coil Type Latching, Single Coil Coil Current 33mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) - Operate Time 3ms Release Time 3ms	Series	G6K
Coil Current 33mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) - Operate Time 3ms Release Time 3ms	Relay Type	Telecom
Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) - Operate Time 3ms Release Time 3ms	Coil Type	Latching, Single Coil
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 7urn Off Voltage (Min) Operate Time 3ms Release Time 3ms	Coil Current	33mA
Contact Rating (Current) Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) Operate Time 3ms Release Time 3ms	Coil Voltage	3VDC
Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) - Operate Time 3ms Release Time 3ms	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time 3ms 3ms	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time 3ms Release Time 3ms	Switching Voltage	125VAC, 60VDC - Max
Operate Time 3ms Release Time 3ms	Turn On Voltage (Max)	2.25 VDC
Release Time 3ms	Turn Off Voltage (Min)	-
	Operate Time	3ms
Factures	Release Time	3ms
reatures -	Features	-
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

G6KU-2P-Y DC3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6KU-2P-Y DC3 Payment Methods



















G6KU-2P-Y DC3 Shipping Methods













If you have any question about G6KU-2P-Y DC3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com