



## **G6RL-14-ASI DC48 Information**



For Reference Only

Part Number G6RL-14-ASI DC48

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPDT 8A 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **G6RL-14-ASI DC48 Specifications**

Manufacturer Part NumberG6RL-14-ASI DC48ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG6RLRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current5mACoil Voltage48VDCContact FormSPDT (1 Form C)Contact Rating (Current)8ASwitching Voltage400VAC, 300VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG6RLRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current5mACoil Voltage48VDCContact FormSPDT (1 Form C)Contact Rating (Current)8ASwitching Voltage400VAC, 300VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G6RL-14-ASI DC48
Package - Series G6RL Relay Type General Purpose Coil Type Non Latching Coil Current 5mA Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC, 300VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package         -           Series         G6RL           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         5mA           Coil Voltage         48VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         8A           Switching Voltage         400VAC, 300VDC - Max           Turn On Voltage (Max)         33.6 VDC           Turn Off Voltage (Min)         4.8 VDC           Operate Time         10ms           Release Time         5ms           Features         Sealed - Fully           Mounting Type         Through Hole           Termination Style         PC Pin	Category	Relays
Series         G6RL           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         5mA           Coil Voltage         48VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         8A           Switching Voltage         400VAC, 300VDC - Max           Turn On Voltage (Max)         33.6 VDC           Turn Off Voltage (Min)         4.8 VDC           Operate Time         10ms           Release Time         5ms           Features         Sealed - Fully           Mounting Type         Through Hole           Termination Style         PC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose  Coil Type Non Latching  Coil Current 5mA  Coil Voltage 48VDC  Contact Form SPDT (1 Form C)  Contact Rating (Current) 8A  Switching Voltage 400VAC, 300VDC - Max  Turn On Voltage (Max) 33.6 VDC  Turn Off Voltage (Min) 4.8 VDC  Operate Time 10ms  Release Time 5ms  Features Sealed - Fully  Mounting Type Through Hole  Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current5mACoil Voltage48VDCContact FormSPDT (1 Form C)Contact Rating (Current)8ASwitching Voltage400VAC, 300VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	G6RL
Coil Current Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC, 300VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC, 300VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPDT (1 Form C)  Contact Rating (Current)  8A  Switching Voltage 400VAC, 300VDC - Max  Turn On Voltage (Max)  33.6 VDC  Turn Off Voltage (Min)  4.8 VDC  Operate Time 10ms  Release Time 5ms  Features Sealed - Fully  Mounting Type Through Hole  Termination Style  PC Pin	Coil Current	5mA
Contact Rating (Current)  Switching Voltage  400VAC, 300VDC - Max  Turn On Voltage (Max)  33.6 VDC  Turn Off Voltage (Min)  4.8 VDC  Operate Time  10ms  Release Time  5ms  Features  Sealed - Fully  Mounting Type  Through Hole  Termination Style  8A  400VAC, 300VDC - Max  33.6 VDC  4.8 VDC  10ms  Formination Style	Coil Voltage	48VDC
Switching Voltage 400VAC, 300VDC - Max  Turn On Voltage (Max) 33.6 VDC  Turn Off Voltage (Min) 4.8 VDC  Operate Time 10ms  Release Time 5ms  Features Sealed - Fully  Mounting Type Through Hole  Termination Style PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  10ms  Release Time  5ms  Features  Sealed - Fully  Mounting Type  Through Hole  Termination Style  33.6 VDC  4.8 VDC  10ms  Formination Style  10ms  Formination Style	Contact Rating (Current)	8A
Turn Off Voltage (Min)  Operate Time  10ms  Release Time  5ms  Features  Sealed - Fully  Mounting Type  Through Hole  Termination Style  4.8 VDC  10ms  Forms  Forms  PC Pin	Switching Voltage	400VAC, 300VDC - Max
Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	33.6 VDC
Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	4.8 VDC
Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Sealed - Fully
•	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

#### **G6RL-14-ASI DC48 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **G6RL-14-ASI DC48 Payment Methods**



















## **G6RL-14-ASI DC48 Shipping Methods**













If you have any question about G6RL-14-ASI DC48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com