

G6RL-14-SR-ASI-SP DC12

G6RL-14-SR-ASI-SP DC12 Information



For Reference Only

Part Number G6RL-14-SR-ASI-SP DC12

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 8A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6RL-14-SR-ASI-SP DC12 Specifications

Manufacturer Part Number G6RL-14-SR-ASI-SP DC12 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Package - Series G6RL Relay Type General Purpose Coil Type Non Latching Coil Current 25.2mA Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC, 300VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG6RLRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current25.2mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)8ASwitching Voltage400VAC, 300VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G6RL-14-SR-ASI-SP DC12
Package-SeriesG6RLRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current25.2mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)8ASwitching Voltage400VAC, 300VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package - Series G6RL Relay Type General Purpose Coil Type Non Latching Coil Current 25.2mA Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC, 300VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesG6RLRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current25.2mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)8ASwitching Voltage400VAC, 300VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 25.2mA Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC, 300VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current25.2mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)8ASwitching Voltage400VAC, 300VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	G6RL
Coil Current 25.2mA Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC, 300VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC, 300VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC, 300VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style	Coil Current	25.2mA
Contact Rating (Current) Switching Voltage 400VAC, 300VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style	Coil Voltage	12VDC
Switching Voltage 400VAC, 300VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) 7 Turn Off Voltage (Min) 9.6 VDC 1.2 VDC Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	8A
Turn Off Voltage (Min) Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style 1.2 VDC 10ms Forms Forms From Sealed - Fully Through Hole PC Pin	Switching Voltage	400VAC, 300VDC - Max
Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	9.6 VDC
Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1.2 VDC
Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Sealed - Fully
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

G6RL-14-SR-ASI-SP DC12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6RL-14-SR-ASI-SP DC12 Payment Methods



















G6RL-14-SR-ASI-SP DC12 Shipping Methods













If you have any question about G6RL-14-SR-ASI-SP DC12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com