

# G6RL-14-SR-ASI-SP DC24

### **G6RL-14-SR-ASI-SP DC24 Information**



For Reference Only

Part Number G6RL-14-SR-ASI-SP DC24

Manufacturer Omron Electronics Inc-EMC Div

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPDT 8A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **G6RL-14-SR-ASI-SP DC24 Specifications**

Manufacturer Part Number       G6RL-14-SR-ASI-SP DC24         Manufacturer       Omron Electronics Inc-EMC Div         Category       Relays         Power Relays, Over 2 Amps         Package       -         Series       G6RL         Relay Type       General Purpose         Coil Type       Non Latching         Coil Current       12.6mA         Coil Voltage       24VDC         Contact Form       SPDT (1 Form C)         Contact Rating (Current)       8A         Switching Voltage       400VAC, 300VDC - Max         Turn On Voltage (Max)       19.2 VDC         Turn Off Voltage (Min)       2.4 VDC         Operate Time       10ms         Release Time       5ms         Features       Sealed - Fully         Mounting Type       Through Hole         Termination Style       PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG6RLRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current12.6mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)8ASwitching Voltage400VAC, 300VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G6RL-14-SR-ASI-SP DC24
Package         -           Series         G6RL           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         12.6mA           Coil Voltage         24VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         8A           Switching Voltage         400VAC, 300VDC - Max           Turn On Voltage (Max)         19.2 VDC           Turn Off Voltage (Min)         2.4 VDC           Operate Time         10ms           Release Time         5ms           Features         Sealed - Fully           Mounting Type         Through Hole           Termination Style         PC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package         -           Series         G6RL           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         12.6mA           Coil Voltage         24VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         8A           Switching Voltage         400VAC, 300VDC - Max           Turn On Voltage (Max)         19.2 VDC           Turn Off Voltage (Min)         2.4 VDC           Operate Time         10ms           Release Time         5ms           Features         Sealed - Fully           Mounting Type         Through Hole           Termination Style         PC Pin	Category	Relays
Series         G6RL           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         12.6mA           Coil Voltage         24VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         8A           Switching Voltage         400VAC, 300VDC - Max           Turn On Voltage (Max)         19.2 VDC           Turn Off Voltage (Min)         2.4 VDC           Operate Time         10ms           Release Time         5ms           Features         Sealed - Fully           Mounting Type         Through Hole           Termination Style         PC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose  Coil Type Non Latching  Coil Current 12.6mA  Coil Voltage 24VDC  Contact Form SPDT (1 Form C)  Contact Rating (Current) 8A  Switching Voltage 400VAC, 300VDC - Max  Turn On Voltage (Max) 19.2 VDC  Turn Off Voltage (Min) 2.4 VDC  Operate Time 10ms  Release Time 5ms  Features Sealed - Fully  Mounting Type Through Hole  Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current12.6mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)8ASwitching Voltage400VAC, 300VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	G6RL
Coil Current12.6mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)8ASwitching Voltage400VAC, 300VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage 24VDC  Contact Form SPDT (1 Form C)  Contact Rating (Current) 8A  Switching Voltage 400VAC, 300VDC - Max  Turn On Voltage (Max) 19.2 VDC  Turn Off Voltage (Min) 2.4 VDC  Operate Time 10ms  Release Time 5ms  Features Sealed - Fully  Mounting Type Through Hole  Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPDT (1 Form C)  Contact Rating (Current)  8A  Switching Voltage 400VAC, 300VDC - Max  Turn On Voltage (Max)  19.2 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  10ms  Release Time  5ms  Features  Sealed - Fully  Mounting Type  Through Hole  Termination Style	Coil Current	12.6mA
Contact Rating (Current)  Switching Voltage  400VAC, 300VDC - Max  Turn On Voltage (Max)  19.2 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  10ms  Release Time  5ms  Features  Sealed - Fully  Mounting Type  Through Hole  Termination Style	Coil Voltage	24VDC
Switching Voltage 400VAC, 300VDC - Max  Turn On Voltage (Max) 19.2 VDC  Turn Off Voltage (Min) 2.4 VDC  Operate Time 10ms  Release Time 5ms  Features Sealed - Fully  Mounting Type Through Hole  Termination Style PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)  19.2 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  10ms  Release Time  5ms  Features  Sealed - Fully  Mounting Type  Through Hole  Termination Style  PC Pin	Contact Rating (Current)	8A
Turn Off Voltage (Min)  Operate Time  10ms  Release Time  5ms  Features  Sealed - Fully  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	400VAC, 300VDC - Max
Operate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	19.2 VDC
Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	2.4 VDC
Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Sealed - Fully
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
Topol distance		Report errors?

### **G6RL-14-SR-ASI-SP DC24 Guarantees**



## **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **G6RL-14-SR-ASI-SP DC24 Payment Methods**



















## **G6RL-14-SR-ASI-SP DC24 Shipping Methods**













If you have any question about G6RL-14-SR-ASI-SP DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com