

### **G6S-2-Y DC5 Information**



For Reference Only

Part Number G6S-2-Y DC5

Manufacturer Omron Electronics Inc-EMC Div

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY TELECOM DPDT 2A 5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **G6S-2-Y DC5 Specifications**

Manufacturer Part NumberG68-2-Y DC5ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysPackage-SeriesG6SRelay TypeTelecomCoil TypeNon LatchingCoil Current40mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time4msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPackage-SeriesG6SRelay TypeTelecomCoil TypeNon LatchingCoil Current40mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time4msRelease Time4msFeatures-Mounting TypeThrough Hole	Manufacturer Part Number	G6S-2-Y DC5
Package-SeriesG6SRelay TypeTelecomCoil TypeNon LatchingCoil Current40mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time4msRelease Time4msFeatures-Mounting TypeThrough Hole	Manufacturer	Omron Electronics Inc-EMC Div
Package - G6S Relay Type Telecom Coil Type Non Latching Coil Current 40mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 4ms Release Time 4ms Features - Mounting Type Through Hole	Category	Relays
SeriesG6SRelay TypeTelecomCoil TypeNon LatchingCoil Current40mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time4msRelease Time4msFeatures-Mounting TypeThrough Hole		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeNon LatchingCoil Current40mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time4msRelease Time4msFeatures-Mounting TypeThrough Hole	Package	-
Coil Type Non Latching Coil Current 40mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 4ms Release Time 4ms Release Time 4ms Features - Mounting Type Through Hole	Series	G6S
Coil Current 40mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 4ms Release Time 4ms Features - Mounting Type Through Hole	Relay Type	Telecom
Coil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time4msRelease Time4msFeatures-Mounting TypeThrough Hole	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  250VAC, 220VDC - Max  Turn On Voltage (Max)  3.75 VDC  Turn Off Voltage (Min)  0.5 VDC  Operate Time  4ms  Release Time  4ms  Features  -  Mounting Type  Through Hole	Coil Current	40mA
Contact Rating (Current)  Switching Voltage  250VAC, 220VDC - Max  Turn On Voltage (Max)  3.75 VDC  Turn Off Voltage (Min)  0.5 VDC  Operate Time  4ms  Release Time  4ms  Features  -  Mounting Type  Through Hole	Coil Voltage	5VDC
Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 4ms Release Time 4ms Features - Mounting Type Through Hole	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Ams  Release Time  4ms  Features  -  Mounting Type  3.75 VDC  4ms  4ms  Through Hole	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features - Mounting Type Through Hole	Switching Voltage	250VAC, 220VDC - Max
Operate Time 4ms Release Time 4ms Features - Mounting Type Through Hole	Turn On Voltage (Max)	3.75 VDC
Release Time 4ms Features - Mounting Type Through Hole	Turn Off Voltage (Min)	0.5 VDC
Features - Mounting Type Through Hole	Operate Time	4ms
Mounting Type Through Hole	Release Time	4ms
	Features	-
Termination Style DC Pin	Mounting Type	Through Hole
remination style	Termination Style	PC Pin
Report errors?		Report errors?

#### **G6S-2-Y DC5 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **G6S-2-Y DC5 Payment Methods**



















### **G6S-2-Y DC5 Shipping Methods**













If you have any question about G6S-2-Y DC5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com