



G6S-2F-Y-TR DC4.5 Information



For Reference Only

Part Number G6S-2F-Y-TR DC4.5

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY TELECOM DPDT 2A 4.5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6S-2F-Y-TR DC4.5 Specifications

Manufacturer Part Number G6S-2F-Y-TR DC4.5 Manufacturer Omron Electronics Inc-EMC Div Category Relays Signal Relays, Up to 2 Amps Package - Series G6S Relay Type Telecom Coil Type Non Latching Coil Current 44.4mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) 0.45 VDC
Category Relays Signal Relays, Up to 2 Amps Package - Series G6S Relay Type Telecom Coil Type Non Latching Coil Current 44.4mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage Turn On Voltage (Max) 3.38 VDC
Package - Series G6S Relay Type Telecom Coil Type Non Latching Coil Current 44.4mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage (Max) 3.38 VDC
Package - G6S Relay Type Telecom Coil Type Non Latching Coil Current 44.4mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.38 VDC
Series G6S Relay Type Telecom Coil Type Non Latching Coil Current 44.4mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.38 VDC
Relay Type Coil Type Non Latching Coil Current 44.4mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.38 VDC
Coil Type Non Latching Coil Current 44.4mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.38 VDC
Coil Current 44.4mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.38 VDC
Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.38 VDC
Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.38 VDC
Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.38 VDC
Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.38 VDC
Turn On Voltage (Max) 3.38 VDC
Turn Off Voltage (Min)
Turi Ori voltage (Will)
Operate Time 4ms
Release Time 4ms
Features -
Mounting Type Surface Mount
Termination Style Gull Wing
Report errors?

G6S-2F-Y-TR DC4.5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6S-2F-Y-TR DC4.5 Payment Methods





















G6S-2F-Y-TR DC4.5 Shipping Methods













If you have any question about G6S-2F-Y-TR DC4.5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com