

G6SK-2 DC3 Information



For Reference Only

Part Number G6SK-2 DC3

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY TELECOM DPDT 2A 3V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6SK-2 DC3 Specifications

Manufacturer Part NumberG6SK-2 DC3ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysSignal Relays, Up to 2 AmpsPackage-SeriesG6SRelay TypeTelecomCoil TypeLatching, Dual CoilCoil Current66.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)2.25 VDC
Category Relays Signal Relays, Up to 2 Amps Package - Series G6S Relay Type Telecom Coil Type Latching, Dual Coil Coil Current 66.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max
Package - Series G6S Relay Type Telecom Coil Type Latching, Dual Coil Coil Current 66.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max
Package - G6S Relay Type Telecom Coil Type Latching, Dual Coil Coil Current 66.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max
Series G6S Relay Type Telecom Coil Type Latching, Dual Coil Coil Current 66.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max
Relay Type Coil Type Latching, Dual Coil Coil Current 66.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max
Coil Type Latching, Dual Coil Coil Current 66.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max
Coil Current 66.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max
Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max
Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max
Contact Rating (Current) Switching Voltage 2A 250VAC, 220VDC - Max
Switching Voltage 250VAC, 220VDC - Max
Turn On Voltage (Max) 2.25 VDC
Turn Off Voltage (Min)
Operate Time 4ms
Release Time 4ms
Features -
Mounting Type Through Hole
Termination Style PC Pin
Report errors?

G6SK-2 DC3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6SK-2 DC3 Payment Methods



















G6SK-2 DC3 Shipping Methods













If you have any question about G6SK-2 DC3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com