

## G6SK-2F-H-TR DC4.5

#### **G6SK-2F-H-TR DC4.5 Information**

Part Number G6SK-2F-H-TR DC4.5

Manufacturer Omron Electronics Inc-EMC Div

Category

Signal Relays, Up to 2 Amps

**Description RELAY TELECOM DPDT 2A 4.5V** 

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **G6SK-2F-H-TR DC4.5 Specifications**

Manufacturer Part Number  Manufacturer  Omron Electronics Inc-EMC Div  Relays  Signal Relays, Up to 2 Amps  Package  - Series  G6S  Relay Type  Telecom  Coil Type  Latching, Dual Coil  Coil Current  31mA  Coil Voltage  4.5VDC  Contact Form  DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  250VAC, 220VDC - Max
Category Relays Signal Relays, Up to 2 Amps Package - Series G6S Relay Type Telecom Coil Type Latching, Dual Coil Coil Current 31mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max
Package - Series G6S Relay Type Telecom Coil Type Latching, Dual Coil Coil Current 31mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max
Package - G6S  Relay Type Telecom  Coil Type Latching, Dual Coil  Coil Current 31mA  Coil Voltage 4.5VDC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 2A  Switching Voltage 250VAC, 220VDC - Max
Series G6S  Relay Type Telecom  Coil Type Latching, Dual Coil  Coil Current 31mA  Coil Voltage 4.5VDC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 2A  Switching Voltage 250VAC, 220VDC - Max
Relay TypeTelecomCoil TypeLatching, Dual CoilCoil Current31mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - Max
Coil Type Latching, Dual Coil Coil Current 31mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max
Coil Current 31mA  Coil Voltage 4.5VDC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 2A  Switching Voltage 250VAC, 220VDC - Max
Coil Voltage 4.5VDC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 2A  Switching Voltage 250VAC, 220VDC - Max
Contact Form DPDT (2 Form C)  Contact Rating (Current) 2A  Switching Voltage 250VAC, 220VDC - Max
Contact Rating (Current)  Switching Voltage  2A  250VAC, 220VDC - Max
Switching Voltage 250VAC, 220VDC - Max
T 0 11 1 11 11 11 11 11 11 11 11 11 11 11
Turn On Voltage (Max) 3.38 VDC
Turn Off Voltage (Min)
Operate Time 4ms
Release Time 4ms
Features -
Mounting Type Surface Mount
Termination Style Gull Wing
Report errors?

#### **G6SK-2F-H-TR DC4.5 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **G6SK-2F-H-TR DC4.5 Payment Methods**



















# **G6SK-2F-H-TR DC4.5 Shipping Methods**













If you have any question about G6SK-2F-H-TR DC4.5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com