

G6SU-2 DC4.5

G6SU-2 DC4.5 Information

		G6SU-2 DC4.5 Omron Electronics Inc-EMC Div Relays	
www.heisener.com	Category	Signal Relays, Up to 2 Amps	- 508556
1 ⁴ Time	Description	RELAY TELECOM DPDT 2A 4.5V	
	Package	-	കാബം
1 I I I		For the pricing/inventory/lead time, please contact	_ EL627754
		US Wabaita: https://www.baisapar.com	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G6SU-2 DC4.5 Specifications

Manufacturer Part NumberGóSU-2 DC4.5ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysActageSignal Relays, Up to 2 AmpsPackage-SeriesGóSRelay TypeTelcomColl TypeLaching, Single CoilCoil Current2.2mAColtate FormDPDT (2 Form C)Contact FormSoVAC, 220VDC - MaxSwitching VoltageSoVAC, 220VDC - MaxTurn Of Voltage (Max).38 VDCTurn Of Voltage (Max)-Release TimeAmsRelays Time-Fatures-FortaresPC Pin		
CategoryRelaysCategorySignal Relays, Up to 2 AmpsPackage-SeriesG6SRelay TypeTelecomCoil TypeLaching, Single CoilCoil Current2.2mACoil Otage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)20VAC, 220VDC - MaxSwitching Yoltage3.38 VDCTurn On Voltage (Max)J.38 VDCCurrent Fine4.500Speare Time-Current SeriesSingle Coil Coil Coil Coil Coil Coil Coil Coil	Manufacturer Part Number	G6SU-2 DC4.5
Signal Relays, Up to 2 AmpsPackage-SeriesG6SRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current22.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage (Max)3.38 VDCTurn On Voltage (Max)-Operate Time4msRelease Time-Features-Mounting TypeFinogh HoleFermination StylePC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG6SRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current22.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.38 VDCCurrent Fine-Operate Time4msRelease Time-Features-Mounting TypeDrong HoleFermination StyleCP in	Category	Relays
SeriesG6SRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current22.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max).3.8 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time-Features.Mounting TypeTurogh HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeLatching, Single CoilCoil Type22.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage50VAC, 220VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time-Mounting Type-Termination StylePC Pin	Package	-
Coil TypeLatching, Single CoilCoil TypeLatching, Single CoilCoil Current22.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time-Features-Mounting TypeThrough HoleTermination StylePC Pin	Series	G6S
Coil Current22.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeDrough HoleTermination StylePC Pin	Relay Type	Telecom
Coil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting Type-Termination StylePio Pin	Coil Type	Latching, Single Coil
Contact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Coil Current	22.2mA
Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Coil Voltage	4.5VDC
Switching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Contact Rating (Current)	2A
Turn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Switching Voltage	250VAC, 220VDC - Max
Operate Time4msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	3.38 VDC
Release Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Turn Off Voltage (Min)	-
Features-Mounting TypeThrough HoleTermination StylePC Pin	Operate Time	4ms
Mounting TypeThrough HoleTermination StylePC Pin	Release Time	4ms
Termination Style PC Pin	Features	-
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

G6SU-2 DC4.5 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

G6SU-2 DC4.5 Payment Methods



G6SU-2 DC4.5 Shipping Methods



If you have any question about G6SU-2 DC4.5, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com