



G6SU-2G-TR DC4.5 Information

Part Number G6SU-2G-TR DC4.5

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY TELECOM DPDT 2A 4.5V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6SU-2G-TR DC4.5 Specifications

Manufacturer Part Number Manufacturer Omron Electronics Inc-EMC Div Relays Signal Relays, Up to 2 Amps Package - Series G6S Relay Type Telecom Coil Type Latching, Single Coil Coil Current 22.2mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max
Category Relays Signal Relays, Up to 2 Amps Package - Series G6S Relay Type Telecom Coil Type Latching, Single Coil Coil Current 22.2mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A
Package - Series G6S Relay Type Telecom Coil Type Latching, Single Coil Coil Current 22.2mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A
Package - G6S Relay Type Telecom Coil Type Latching, Single Coil Coil Current 22.2mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A
Series G6S Relay Type Telecom Coil Type Latching, Single Coil Coil Current 22.2mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A
Relay Type Coil Type Latching, Single Coil Coil Current 22.2mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A
Coil Type Latching, Single Coil Coil Current 22.2mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A
Coil Current 22.2mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A
Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A
Contact Form DPDT (2 Form C) Contact Rating (Current) 2A
Contact Rating (Current) 2A
-
Switching Voltage 250VAC, 220VDC - Max
Turn On Voltage (Max) 3.38 VDC
Turn Off Voltage (Min)
Operate Time 4ms
Release Time 4ms
Features -
Mounting Type Surface Mount
Termination Style J Lead
Report errors?

G6SU-2G-TR DC4.5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6SU-2G-TR DC4.5 Payment Methods





















G6SU-2G-TR DC4.5 Shipping Methods













If you have any question about G6SU-2G-TR DC4.5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com