



G6WU-1P DC4.5 Information

Heisener.com

Part Number G6WU-1P DC4.5

Manufacturer Omron Electronics Inc-EMC Div

Category

Signal Relays, Up to 2 Amps

Description RELAY RF SPDT 10MA 4.5V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6WU-1P DC4.5 Specifications

Manufacturer Part Number G6WU-1P DC4.5 Manufacturer Omron Electronics Inc-EMC Div Category Relays Signal Relays, Up to 2 Amps Package - Series G6W Relay Type RF Coil Type Latching, Single Coil Coil Current 44.4mA Coil Voltage 4.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10mA Switching Voltage 30VAC, 30VDC - Max Turn On Voltage (Max) 3.6 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features Scaled Falls		
Category Relays Signal Relays, Up to 2 Amps Package - Series G6W Relay Type RF Coil Type Latching, Single Coil Coil Current 44.4mA Coil Voltage 4.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 30VAC, 30VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms	Manufacturer Part Number	G6WU-1P DC4.5
Package - Series G6W Relay Type RF Coil Type Latching, Single Coil Coil Current 44.4mA Coil Voltage 4.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10mA Switching Voltage 30VAC, 30VDC - Max Turn On Voltage (Max) 3.6 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms	Manufacturer	Omron Electronics Inc-EMC Div
Package - G6W Relay Type RF Coil Type Latching, Single Coil Coil Current 44.4mA Coil Voltage 4.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10mA Switching Voltage 30VAC, 30VDC - Max Turn On Voltage (Max) 3.6 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms	Category	Relays
SeriesG6WRelay TypeRFCoil TypeLatching, Single CoilCoil Current44.4mACoil Voltage4.5VDCContact FormSPDT (1 Form C)Contact Rating (Current)10mASwitching Voltage30VAC, 30VDC - MaxTurn On Voltage (Max)3.6 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time10ms		Signal Relays, Up to 2 Amps
Relay Type RF Coil Type Latching, Single Coil Coil Current 44.4mA Coil Voltage 4.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10mA Switching Voltage 30VAC, 30VDC - Max Turn On Voltage (Max) 3.6 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms	Package	-
Coil Type Latching, Single Coil Coil Current 44.4mA Coil Voltage 4.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10mA Switching Voltage 30VAC, 30VDC - Max Turn On Voltage (Max) 3.6 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms	Series	G6W
Coil Current 44.4mA Coil Voltage 4.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10mA Switching Voltage 30VAC, 30VDC - Max Turn On Voltage (Max) 3.6 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms	Relay Type	RF
Coil Voltage 4.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10mA Switching Voltage 30VAC, 30VDC - Max Turn On Voltage (Max) 3.6 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms	Coil Type	Latching, Single Coil
Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 30VAC, 30VDC - Max Turn On Voltage (Max) 3.6 VDC Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms	Coil Current	44.4mA
Contact Rating (Current) Switching Voltage 30VAC, 30VDC - Max Turn On Voltage (Max) 7urn Off Voltage (Min) Operate Time 10ms Release Time 10ms	Coil Voltage	4.5VDC
Switching Voltage 30VAC, 30VDC - Max Turn On Voltage (Max) 3.6 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms	Contact Rating (Current)	10mA
Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms	Switching Voltage	30VAC, 30VDC - Max
Operate Time 10ms Release Time 10ms	Turn On Voltage (Max)	3.6 VDC
Release Time 10ms	Turn Off Voltage (Min)	-
	Operate Time	10ms
Cooled Eully	Release Time	10ms
reatures Sealed - Fully	Features	Sealed - Fully
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

G6WU-1P DC4.5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6WU-1P DC4.5 Payment Methods



















G6WU-1P DC4.5 Shipping Methods













If you have any question about G6WU-1P DC4.5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com