

G6Z-1F DC3

a Quote

G6Z-1F DC3 Information

	Part Number	G6Z-1F DC3	
non	Manufacturer	Omron Electronics Inc-EMC Div	- Milia
	Category	Relays	
ww.heisener.com		Signal Relays, Up to 2 Amps	<u> 1999 T</u>
	Description	RELAY RF SPDT 10MA 3V	
	Package	-	- Hiida
		For the pricing/inventory/lead time, please contact	- El Mai
		us	
For Reference Only		Website: https://www.heisener.com	Request
		E-mail: salesdept@heisener.com	request

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G6Z-1F DC3 Specifications

Manufacturer Part Number G62-1F DC3 Manufacturer Omron Electronics Inc-EMC Div Category Relays Category Relays Package - Series G6Z Relay Type G6Z Coil Type Non Latching Coil Current 66.7mA Coil Current SVDC Cotact Form SVDC1 Form C) Cotact Rating (Current) J0mA Switching Voltage 30VAC, 30VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time Ioms Release Time Sealed - Fully Mounting Type Surface Mount		
CategoryRelaysCategoryRelays, Up to 2 AmpsPackage-Package-SeriesG6ZRelay TypeRFCoil TypeNon LatchingCoil Current66.7mACoil Voltage3VDCContact FormSPDT (1 Form C)Contact Rating (Current)10mASwitching Voltage (Max)2.25 VDCTurn On Voltage (Max)0.3 VDCOperate Time10msRelease Time10msRelease Time10msFeaturesSealed - FullyMounting TypeSurface MountFermination StyleGull Wing	Manufacturer Part Number	G6Z-1F DC3
Signal Relays, Up to 2 AmpsPackage-SeriesG6ZRelay TypeRFCoil TypeNon LatchingCoil Current66.7mACoil Voltage3VDCContact FormSPDT (1 Form C)Contact Rating (Current)10mASwitching Voltage30VAC, 30VDC - MaxTurn On Voltage (Max)2.25 VDCOperate Time10msRelease Time10msFeaturesSeaded - FullyMounting TypeSurface MountTermination StyleGull Wing	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG6ZRelay TypeRFCoil TypeNon LatchingCoil Current66.7mACoil Voltage3VDCContact FormSPDT (1 Form C)Contact Rating (Current)10mASwitching Voltage (Max)2.25 VDCTurn On Voltage (Max)0.3 VDCOperate Time10msRelease Time10msFeaturesSeidel - FullyMounting TypeSurface MountFermination StyleGull Wing	Category	Relays
SeriesG6ZRelay TypeRFCoil TypeNon LatchingCoil Current66.7mACoil Voltage3VDCContact FormSPDT (1 Form C)Contact Rating (Current)10mASwitching Voltage30VAC, 30VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)0.3 VDCOperate Time10msRelease Time10msFeaturesSeadel - FullyMounting TypeSuface MountTermination StyleGull Wing		Signal Relays, Up to 2 Amps
Relay TypeFFCoil TypeNon LatchingCoil Current66.7mACoil Voltage3VDCContact FormSPDT (1 Form C)Contact Rating (Current)10mASwitching Voltage30VAC, 30VDC - MaxTurn On Voltage (Max)2.25 VDCOperate Time10msRelease Time10msFaturesSeidel - FullyMounting TypeSurface MountTermination StyleGull Wing	Package	-
Coil TypeNon LatchingCoil Type66.7mACoil Voltage3VDCContact FormSPDT (1 Form C)Contact Rating (Current)10mASwitching Voltage30VAC, 30VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)0.3 VDCOperate Time10msRelease Time10msFeaturesSealed - FullyMounting TypeGull Wing	Series	G6Z
Coil Current66.7mACoil Voltage3VDCContact FormSPDT (1 Form C)Contact Rating (Current)10mASwitching Voltage30VAC, 30VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)0.3 VDCOperate Time10msRelease Time10msFeaturesSealed - FullyMounting TypeGull WingOther StyleGull Wing	Relay Type	RF
Coil Voltage3VDCContact FormSPDT (1 Form C)Contact Rating (Current)10mASwitching Voltage30VAC, 30VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)0.3 VDCOperate Time10msRelease Time10msFeaturesSealed - FullyMounting TypeSurface MountTermination StyleGull Wing	Coil Type	Non Latching
Contact FormSPDT (1 Form C)Contact Rating (Current)10mASwitching Voltage30VAC, 30VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)0.3 VDCOperate Time10msRelease Time10msFeaturesSealed - FullyMounting TypeSurface MountTermination StyleGull Wing	Coil Current	66.7mA
Contact Rating (Current)10mASwitching Voltage30VAC, 30VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)0.3 VDCOperate Time10msRelease Time10msFeaturesSealed - FullyMounting TypeSurface MountTermination StyleGull Wing	Coil Voltage	3VDC
Switching Voltage30VAC, 30VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)0.3 VDCOperate Time10msRelease Time10msFeaturesSealed - FullyMounting TypeSurface MountTermination StyleGull Wing	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)0.3 VDCOperate Time10msRelease Time10msFeaturesSealed - FullyMounting TypeSurface MountTermination StyleGull Wing	Contact Rating (Current)	10mA
Turn Off Voltage (Min)0.3 VDCOperate Time10msRelease Time10msFeaturesSealed - FullyMounting TypeSurface MountTermination StyleGull Wing	Switching Voltage	30VAC, 30VDC - Max
Operate Time10msRelease Time10msFeaturesSealed - FullyMounting TypeSurface MountTermination StyleGull Wing	Turn On Voltage (Max)	2.25 VDC
Release Time10msFeaturesSealed - FullyMounting TypeSurface MountTermination StyleGull Wing	Turn Off Voltage (Min)	0.3 VDC
FeaturesSealed - FullyMounting TypeSurface MountTermination StyleGull Wing	Operate Time	10ms
Mounting TypeSurface MountTermination StyleGull Wing	Release Time	10ms
Termination Style Gull Wing	Features	Sealed - Fully
	Mounting Type	Surface Mount
Report errors?	Termination Style	Gull Wing
		Report errors?

G6Z-1F DC3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

G6Z-1F DC3 Payment Methods Image: I

If you have any question about G6Z-1F DC3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com