



# **G6ZU-1P DC4.5 Information**



For Reference Only

Part Number G6ZU-1P DC4.5

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Signal Relays, Up to 2 Amps

**Description** RELAY RF SPDT 10MA 4.5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **G6ZU-1P DC4.5 Specifications**

Manufacturer         G6ZU-IP DC4.5           Manufacturer         Omron Electronics Inc-EMC Div           Category         Relays           Signal Relays, Up to 2 Amps           Package         -           Series         G6Z           Relay Type         RF           Coil Type         Latching, Single Coil           Coil Current         44.4mA           Coil Voltage         4.5VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         10mA           Switching Voltage         30VAC, 30VDC - Max           Turn On Voltage (Max)         3.38 VDC           Turn Off Voltage (Min)         -           Operate Time         10ms           Release Time         10ms           Features         Sealed - Fully           Mounting Type         Through Hole           Termination Style         PC Pin		
CategoryRelaysPackage-SeriesG6ZRelay TypeRFCoil TypeLatching, Single CoilCoil Current44.4mACoil Voltage4.5VDCContact FormSPDT (1 Form C)Contact Rating (Current)10mASwitching Voltage30VAC, 30VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time10msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G6ZU-1P DC4.5
Package-SeriesG6ZRelay TypeRFCoil TypeLatching, Single CoilCoil Current44.4mACoil Voltage4.5VDCContact FormSPDT (1 Form C)Contact Rating (Current)10mASwitching Voltage30VAC, 30VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time10msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package         -           Series         G6Z           Relay Type         RF           Coil Type         Latching, Single Coil           Coil Current         44.4mA           Coil Voltage         4.5VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         10mA           Switching Voltage         30VAC, 30VDC - Max           Turn On Voltage (Max)         3.38 VDC           Turn Off Voltage (Min)         -           Operate Time         10ms           Release Time         10ms           Features         Sealed - Fully           Mounting Type         Through Hole           Termination Style         PC Pin	Category	Relays
SeriesG6ZRelay TypeRFCoil TypeLatching, Single CoilCoil Current44.4mACoil Voltage4.5VDCContact FormSPDT (1 Form C)Contact Rating (Current)10mASwitching Voltage30VAC, 30VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time10msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeRFCoil TypeLatching, Single CoilCoil Current44.4mACoil Voltage4.5VDCContact FormSPDT (1 Form C)Contact Rating (Current)10mASwitching Voltage30VAC, 30VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time10msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Latching, Single Coil Coil Current 44.4mA Coil Voltage 4.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10mA Switching Voltage 30VAC, 30VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Series	G6Z
Coil Current Coil Voltage 4.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10mA Switching Voltage 30VAC, 30VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 10ms Features Sealed - Fully Mounting Type Through Hole Termination Style  44.4mA 4.4mA 4.5VDC 4.5VDC  10mA  10mA  3.0VAC, 30VDC - Max  3.38 VDC  Turn Off Voltage (Min) - Permination Style	Relay Type	RF
Coil Voltage 4.5VDC  Contact Form SPDT (1 Form C)  Contact Rating (Current) 10mA  Switching Voltage 30VAC, 30VDC - Max  Turn On Voltage (Max) 3.38 VDC  Turn Off Voltage (Min) -  Operate Time 10ms  Release Time 10ms  Features Sealed - Fully  Mounting Type Through Hole  Termination Style PC Pin	Coil Type	Latching, Single Coil
Contact Form SPDT (1 Form C)  Contact Rating (Current)  Switching Voltage  30VAC, 30VDC - Max  Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  10ms  Release Time  10ms  Features  Sealed - Fully  Mounting Type  Through Hole  Termination Style	Coil Current	44.4mA
Contact Rating (Current)  Switching Voltage  30VAC, 30VDC - Max  Turn On Voltage (Max)  3.38 VDC  Turn Off Voltage (Min)  Operate Time  10ms  Release Time  10ms  Features  Sealed - Fully  Mounting Type  Through Hole  Termination Style	Coil Voltage	4.5VDC
Switching Voltage 30VAC, 30VDC - Max  Turn On Voltage (Max) 3.38 VDC  Turn Off Voltage (Min) - Operate Time 10ms  Release Time 10ms  Features Sealed - Fully  Mounting Type Through Hole  Termination Style PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  10ms  Release Time  10ms  Features  Sealed - Fully  Mounting Type  Through Hole  Termination Style  3.38 VDC	Contact Rating (Current)	10mA
Turn Off Voltage (Min)  Operate Time  10ms  Release Time  10ms  Features  Sealed - Fully  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	30VAC, 30VDC - Max
Operate Time10msRelease Time10msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	3.38 VDC
Release Time 10ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	10ms
Termination Style PC Pin	Features	Sealed - Fully
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
•		Report errors?

#### **G6ZU-1P DC4.5 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **G6ZU-1P DC4.5 Payment Methods**



















### **G6ZU-1P DC4.5 Shipping Methods**













If you have any question about G6ZU-1P DC4.5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com