



G7J-2A2B-B AC50 Information



For Reference Only

Part Number G7J-2A2B-B AC50

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PST 25A 50V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G7J-2A2B-B AC50 Specifications

Manufacturer Part Number G7J-2A2B-B AC50 Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series G7J Relay Type General Purpose Coil Type Non Latching Coil Current 36mA Coil Voltage 50VAC Contact Form 4PST (2 Form A, 2 Form B) Contact Rating (Current) 25A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 37.5 VAC Turn Off Voltage (Min) 7.5 VAC Operate Time 50ms Release Time 50ms Features Test Button Mounting Type Chassis Mount Termination Style Screw Terminal		
Category Relays Power Relays, Over 2 Amps Package	Manufacturer Part Number	G7J-2A2B-B AC50
Package-SeriesG7JRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36mACoil Voltage50VACContact Form4PST (2 Form A, 2 Form B)Contact Rating (Current)25ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)37.5 VACTurn Off Voltage (Min)7.5 VACOperate Time50msRelease Time50msFeaturesTest ButtonMounting TypeChassis MountTermination StyleScrew Terminal	Manufacturer	Omron Automation and Safety
Package - Series G7J Relay Type General Purpose Coil Type Non Latching Coil Current 36mA Coil Voltage 50VAC Contact Form 4PST (2 Form A, 2 Form B) Contact Rating (Current) 25A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 37.5 VAC Turn Off Voltage (Min) 7.5 VAC Operate Time 50ms Release Time 50ms Features Test Button Mounting Type Chassis Mount Termination Style Screw Terminal	Category	Relays
SeriesG7JRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36mACoil Voltage50VACContact Form4PST (2 Form A, 2 Form B)Contact Rating (Current)25ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)37.5 VACTurn Off Voltage (Min)7.5 VACOperate Time50msRelease Time50msFeaturesTest ButtonMounting TypeChassis MountTermination StyleScrew Terminal		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 36mA Coil Voltage 50VAC Contact Form 4PST (2 Form A, 2 Form B) Contact Rating (Current) 25A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 37.5 VAC Turn Off Voltage (Min) 7.5 VAC Operate Time 50ms Release Time 50ms Release Time 50ms Features Test Button Mounting Type Chassis Mount Termination Style Soven Terminal	Package	-
Coil TypeNon LatchingCoil Current36mACoil Voltage50VACContact Form4PST (2 Form A, 2 Form B)Contact Rating (Current)25ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)37.5 VACTurn Off Voltage (Min)7.5 VACOperate Time50msRelease Time50msFeaturesTest ButtonMounting TypeChassis MountTermination StyleScrew Terminal	Series	G7J
Coil Current36mACoil Voltage50VACContact Form4PST (2 Form A, 2 Form B)Contact Rating (Current)25ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)37.5 VACTurn Off Voltage (Min)7.5 VACOperate Time50msRelease Time50msFeaturesTest ButtonMounting TypeChassis MountTermination StyleScrew Terminal	Relay Type	General Purpose
Coil Voltage 50VAC Contact Form 4PST (2 Form A, 2 Form B) Contact Rating (Current) 25A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 37.5 VAC Turn Off Voltage (Min) 7.5 VAC Operate Time 50ms Release Time 50ms Features Test Button Mounting Type Chassis Mount Termination Style Sover Terminal	Coil Type	Non Latching
Contact Form 4PST (2 Form A, 2 Form B) Contact Rating (Current) 25A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 37.5 VAC Turn Off Voltage (Min) 7.5 VAC Operate Time 50ms Release Time 50ms Release Time 50ms Features Test Button Mounting Type Chassis Mount Termination Style Screw Terminal	Coil Current	36mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 7.5 VAC Turn Off Voltage (Min) 7.5 VAC Operate Time 50ms Release Time 50ms Features Test Button Mounting Type Chassis Mount Termination Style	Coil Voltage	50VAC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 7.5 VAC Operate Time 50ms Release Time 50ms Features Test Button Mounting Type Chassis Mount Termination Style	Contact Form	4PST (2 Form A, 2 Form B)
Turn On Voltage (Max) Turn Off Voltage (Min) 7.5 VAC Operate Time 50ms Release Time 50ms Test Button Mounting Type Chassis Mount Termination Style Screw Terminal	Contact Rating (Current)	25A
Turn Off Voltage (Min) 7.5 VAC Operate Time 50ms Release Time 50ms Features Test Button Mounting Type Chassis Mount Termination Style Screw Terminal	Switching Voltage	250VAC, 125VDC - Max
Operate Time50msRelease Time50msFeaturesTest ButtonMounting TypeChassis MountTermination StyleScrew Terminal	Turn On Voltage (Max)	37.5 VAC
Release Time 50ms Features Test Button Mounting Type Chassis Mount Termination Style Screw Terminal	Turn Off Voltage (Min)	7.5 VAC
Features Test Button Mounting Type Chassis Mount Termination Style Screw Terminal	Operate Time	50ms
Mounting Type Chassis Mount Termination Style Screw Terminal	Release Time	50ms
Termination Style Screw Terminal	Features	Test Button
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Screw Terminal
		Report errors?

G7J-2A2B-B AC50 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G7J-2A2B-B AC50 Payment Methods



















G7J-2A2B-B AC50 Shipping Methods













If you have any question about G7J-2A2B-B AC50, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com