



G7J-2A2B-B-W1 AC24 Information



For Reference Only

Part Number G7J-2A2B-B-W1 AC24

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PST 25A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G7J-2A2B-B-W1 AC24 Specifications

Manufacturer Part Number Manufacturer Omron Automation and Safety Relays Power Relays, Over 2 Amps Package Series G7J Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 24VAC Contact Form 4PST (2 Form A, 2 Form B) Contact Rating (Current) 25A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 50ms Release Time 50ms Features Test Button, W-Bracket Included Mounting Type Chassis Mount Termination Style Report errors?		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG7JRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75 mACoil Voltage24V ACContact Form4PST (2 Form A, 2 Form B)Contact Rating (Current)25ASwitching Voltage250V AC, 125V DC - MaxTurn On Voltage (Max)18 V ACTurn Off Voltage (Min)3.6 V ACOperate Time50 msRelease Time50 msFeaturesTest Button, W-Bracket IncludedMounting TypeChassis MountTermination StyleScrew Terminal	Manufacturer Part Number	G7J-2A2B-B-W1 AC24
Package Series G7J Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 24VAC Contact Form 4PST (2 Form A, 2 Form B) Contact Rating (Current) 25A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 50ms Release Time 50ms Features Test Button, W-Bracket Included Mounting Type Chassis Mount Termination Style Screw Terminal	Manufacturer	Omron Automation and Safety
Package - G7J Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 24VAC Contact Form 4PST (2 Form A, 2 Form B) Contact Rating (Current) 25A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 50ms Release Time 50ms Features Test Button, W-Bracket Included Mounting Type Chassis Mount Termination Style Sone Seneral Purpose G913 G913 G913 G913 G913 G913 G913 G913	Category	Relays
SeriesG7JRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage24VACContact Form4PST (2 Form A, 2 Form B)Contact Rating (Current)25ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)3.6 VACOperate Time50msRelease Time50msFeaturesTest Button, W-Bracket IncludedMounting TypeChassis MountTermination StyleScrew Terminal		Power Relays, Over 2 Amps
Relay Type Coil Type Non Latching Coil Current 75mA Coil Voltage 24VAC Contact Form 4PST (2 Form A, 2 Form B) Contact Rating (Current) 25A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 50ms Release Time 50ms Features Test Button, W-Bracket Included Mounting Type Chassis Mount Termination Style Soil Turn Off Voltage Contact Form Non Latching Soma Test Button, W-Bracket Included Screw Terminal	Package	-
Coil Type Coil Current 75mA Coil Voltage 24VAC Contact Form 4PST (2 Form A, 2 Form B) Contact Rating (Current) 25A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 50ms Release Time 50ms Features Test Button, W-Bracket Included Mounting Type Chassis Mount Termination Style Screw Terminal	Series	G7J
Coil Current Coil Voltage 24VAC Contact Form 4PST (2 Form A, 2 Form B) Contact Rating (Current) 25A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 50ms Release Time 50ms Features Test Button, W-Bracket Included Mounting Type Chassis Mount Termination Style Screw Terminal	Relay Type	General Purpose
Coil Voltage 24VAC Contact Form 4PST (2 Form A, 2 Form B) Contact Rating (Current) 25A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 50ms Release Time 50ms Release Time 50ms Features Test Button, W-Bracket Included Mounting Type Chassis Mount Termination Style Screw Terminal	Coil Type	Non Latching
Contact Form 4PST (2 Form A, 2 Form B) Contact Rating (Current) 25A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 50ms Release Time 50ms Release Time Test Button, W-Bracket Included Mounting Type Chassis Mount Termination Style Screw Terminal	Coil Current	75mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 50ms Release Time 50ms Features Test Button, W-Bracket Included Mounting Type Chassis Mount Termination Style Screw Terminal	Coil Voltage	24VAC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 50ms Release Time 50ms Features Test Button, W-Bracket Included Mounting Type Chassis Mount Termination Style Screw Terminal	Contact Form	4PST (2 Form A, 2 Form B)
Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 50ms Release Time 50ms Features Test Button, W-Bracket Included Mounting Type Chassis Mount Termination Style Screw Terminal	Contact Rating (Current)	25A
Turn Off Voltage (Min) Operate Time 50ms Release Time 50ms Features Test Button, W-Bracket Included Mounting Type Chassis Mount Termination Style Screw Terminal	Switching Voltage	250VAC, 125VDC - Max
Operate Time 50ms Release Time 50ms Features Test Button, W-Bracket Included Mounting Type Chassis Mount Termination Style Screw Terminal	Turn On Voltage (Max)	18 VAC
Release Time 50ms Features Test Button, W-Bracket Included Mounting Type Chassis Mount Termination Style Screw Terminal	Turn Off Voltage (Min)	3.6 VAC
Features Test Button, W-Bracket Included Mounting Type Chassis Mount Termination Style Screw Terminal	Operate Time	50ms
Mounting Type Chassis Mount Termination Style Screw Terminal	Release Time	50ms
Termination Style Screw Terminal	Features	Test Button, W-Bracket Included
·	Mounting Type	Chassis Mount
Report errors?	Termination Style	Screw Terminal
		Report errors?

G7J-2A2B-B-W1 AC24 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G7J-2A2B-B-W1 AC24 Payment Methods





















G7J-2A2B-B-W1 AC24 Shipping Methods













If you have any question about G7J-2A2B-B-W1 AC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com