



G7J-3A1B-B DC48 Information

Heisener.com

Part Number G7J-3A1B-B DC48

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PST 25A 48V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G7J-3A1B-B DC48 Specifications

Manufacturer Part Number Manufacturer Omron Automation and Safety Relays Power Relays, Over 2 Amps Package		
Category Relays Power Relays, Over 2 Amps Package	Manufacturer Part Number	G7J-3A1B-B DC48
Package - Series G7J Relay Type General Purpose Coil Type Non Latching Coil Current 42mA Coil Voltage 48VDC Contact Form 4PST (3 Form A, 1 Form B) Contact Rating (Current) 25A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 50ms Release Time 50ms Features Test Button Mounting Type Chassis Mount Termination Style C7J Seneral Purpose General Purpose 50J Seneral	Manufacturer	Omron Automation and Safety
Package-SeriesG7JRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current42mACoil Voltage48VDCContact Form4PST (3 Form A, 1 Form B)Contact Rating (Current)25ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time50msRelease Time50msFeaturesTest ButtonMounting TypeChassis MountTermination StyleScrew Terminal	Category	Relays
SeriesG7JRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current42mACoil Voltage48VDCContact Form4PST (3 Form A, 1 Form B)Contact Rating (Current)25ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time50msRelease Time50msFeaturesTest ButtonMounting TypeChassis MountTermination StyleScrew Terminal		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 42mA Coil Voltage 48VDC Contact Form 4PST (3 Form A, 1 Form B) Contact Rating (Current) 25A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 50ms Release Time 50ms Release Time 50ms Features Test Button Mounting Type Chassis Mount Termination Style Screw Terminal	Package	-
Coil TypeNon LatchingCoil Current42mACoil Voltage48VDCContact Form4PST (3 Form A, 1 Form B)Contact Rating (Current)25ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time50msRelease Time50msFeaturesTest ButtonMounting TypeChassis MountTermination StyleScrew Terminal	Series	G7J
Coil Current Coil Voltage 48VDC Contact Form 4PST (3 Form A, 1 Form B) Contact Rating (Current) 25A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 50ms Release Time 50ms Features Test Button Mounting Type Chassis Mount Termination Style Screw Terminal	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form 4PST (3 Form A, 1 Form B) Contact Rating (Current) 25A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 50ms Release Time 50ms Features Test Button Mounting Type Chassis Mount Termination Style Screw Terminal	Coil Type	Non Latching
Contact Form 4PST (3 Form A, 1 Form B) Contact Rating (Current) 25A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 50ms Release Time 50ms Features Test Button Mounting Type Chassis Mount Termination Style Screw Terminal	Coil Current	42mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 50ms Release Time 50ms Features Test Button Mounting Type Chassis Mount Termination Style	Coil Voltage	48VDC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 50ms Release Time 50ms Features Test Button Mounting Type Chassis Mount Termination Style Screw Terminal	Contact Form	4PST (3 Form A, 1 Form B)
Turn On Voltage (Max) Turn Off Voltage (Min) 4.8 VDC Operate Time 50ms Release Time 50ms Test Button Mounting Type Chassis Mount Termination Style Screw Terminal	Contact Rating (Current)	25A
Turn Off Voltage (Min) Operate Time 50ms Release Time 50ms Features Test Button Mounting Type Chassis Mount Termination Style Screw Terminal	Switching Voltage	250VAC, 125VDC - Max
Operate Time50msRelease Time50msFeaturesTest ButtonMounting TypeChassis MountTermination StyleScrew Terminal	Turn On Voltage (Max)	36 VDC
Release Time 50ms Features Test Button Mounting Type Chassis Mount Termination Style Screw Terminal	Turn Off Voltage (Min)	4.8 VDC
Features Test Button Mounting Type Chassis Mount Termination Style Screw Terminal	Operate Time	50ms
Mounting Type Chassis Mount Termination Style Screw Terminal	Release Time	50ms
Termination Style Screw Terminal	Features	Test Button
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Screw Terminal
		Report errors?

G7J-3A1B-B DC48 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G7J-3A1B-B DC48 Payment Methods





















G7J-3A1B-B DC48 Shipping Methods













If you have any question about G7J-3A1B-B DC48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com