



# **G7J-3A1B-P AC50 Information**

Heisener.com

Part Number G7J-3A1B-P AC50

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE 4PST 25A 50V

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **G7J-3A1B-P AC50 Specifications**

Manufacturer Part Number       G7J-3A1B-P AC50         Manufacturer       Omron Automation and Safety         Category       Relays         Power Relays, Over 2 Amps         Package       -         Series       G7J         Relay Type       General Purpose         Coil Type       Non Latching         Coil Current       36mA         Coil Voltage       50VAC         Contact Form       4PST (3 Form A, 1 Form B)         Contact Rating (Current)       25A         Switching Voltage       250VAC, 125VDC - Max         Turn On Voltage (Max)       37.5 VAC         Turn Off Voltage (Min)       7.5 VAC         Operate Time       50ms         Release Time       50ms         Features       Test Button         Mounting Type       Through Hole         Termination Style       PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG7JRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36mACoil Voltage50VACContact Form4PST (3 Form A, 1 Form B)Contact Rating (Current)25ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)37.5 VACTurn Off Voltage (Min)7.5 VACOperate Time50msRelease Time50msFeaturesTest ButtonMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G7J-3A1B-P AC50
Package - G7J Relay Type General Purpose Coil Type Non Latching Coil Current 36mA Coil Voltage 50VAC Contact Form 4PST (3 Form A, 1 Form B) Contact Rating (Current) 25A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 37.5 VAC Turn Off Voltage (Min) 7.5 VAC Operate Time 50ms Release Time 50ms Features Test Button Mounting Type Through Hole Termination Style  Poperate Time 9C Pin	Manufacturer	Omron Automation and Safety
Package-SeriesG7JRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36mACoil Voltage50VACContact Form4PST (3 Form A, 1 Form B)Contact Rating (Current)25ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)37.5 VACTurn Off Voltage (Min)7.5 VACOperate Time50msRelease Time50msFeaturesTest ButtonMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesG7JRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36mACoil Voltage50VACContact Form4PST (3 Form A, 1 Form B)Contact Rating (Current)25ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)37.5 VACTurn Off Voltage (Min)7.5 VACOperate Time50msRelease Time50msFeaturesTest ButtonMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 36mA Coil Voltage 50VAC Contact Form 4PST (3 Form A, 1 Form B) Contact Rating (Current) 25A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 37.5 VAC Turn Off Voltage (Min) 7.5 VAC Operate Time 50ms Release Time 50ms Features Test Button Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current36mACoil Voltage50VACContact Form4PST (3 Form A, 1 Form B)Contact Rating (Current)25ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)37.5 VACTurn Off Voltage (Min)7.5 VACOperate Time50msRelease Time50msFeaturesTest ButtonMounting TypeThrough HoleTermination StylePC Pin	Series	G7J
Coil Current Coil Voltage 50VAC  Contact Form 4PST (3 Form A, 1 Form B)  Contact Rating (Current) 25A  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 37.5 VAC  Turn Off Voltage (Min) 7.5 VAC  Operate Time 50ms  Release Time 50ms  Features Test Button  Mounting Type Through Hole Termination Style  700 Torm Off Voltage Torm Off Voltage Torm Off Voltage Test Button Through Hole Termination Style	Relay Type	General Purpose
Coil Voltage 50VAC  Contact Form 4PST (3 Form A, 1 Form B)  Contact Rating (Current) 25A  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 37.5 VAC  Turn Off Voltage (Min) 7.5 VAC  Operate Time 50ms  Release Time 50ms  Features Test Button  Mounting Type Through Hole  Termination Style PC Pin	Coil Type	Non Latching
Contact Form 4PST (3 Form A, 1 Form B)  Contact Rating (Current) 25A  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 37.5 VAC  Turn Off Voltage (Min) 7.5 VAC  Operate Time 50ms  Release Time 50ms  Features Test Button  Mounting Type Through Hole  Termination Style PC Pin	Coil Current	36mA
Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  7.5 VAC  Turn Off Voltage (Min)  7.5 VAC  Operate Time  50ms  Release Time  50ms  Features  Test Button  Mounting Type  Through Hole  Termination Style	Coil Voltage	50VAC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 37.5 VAC Turn Off Voltage (Min) 7.5 VAC Operate Time 50ms Release Time 50ms Features Test Button Mounting Type Through Hole Termination Style PC Pin	Contact Form	4PST (3 Form A, 1 Form B)
Turn On Voltage (Max)  Turn Off Voltage (Min)  7.5 VAC  Operate Time  50ms  Release Time  50ms  Features  Test Button  Mounting Type  Through Hole  Termination Style  37.5 VAC  7.5 VAC  Through Hole  PC Pin	Contact Rating (Current)	25A
Turn Off Voltage (Min)  Operate Time  50ms  Release Time  50ms  Features  Test Button  Mounting Type  Through Hole  Termination Style  7.5 VAC  7.5 VAC  7.5 VAC  POPIN	Switching Voltage	250VAC, 125VDC - Max
Operate Time 50ms Release Time 50ms Features Test Button Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	37.5 VAC
Release Time 50ms Features Test Button Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	7.5 VAC
Features Test Button  Mounting Type Through Hole  Termination Style PC Pin	Operate Time	50ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	50ms
Termination Style PC Pin	Features	Test Button
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

#### **G7J-3A1B-P AC50 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **G7J-3A1B-P AC50 Payment Methods**



















## **G7J-3A1B-P AC50 Shipping Methods**













If you have any question about G7J-3A1B-P AC50, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com