

G7J-3A1B-PZ DC12

G7J-3A1B-PZ DC12 Information

Heisener.com	G7J-3A1B-PZ DC12 Omron Automation and Safety Relays Power Relays, Over 2 Amps RELAY GEN PURPOSE 4PST 25A 12V - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G7J-3A1B-PZ DC12 Specifications

Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Power Relays, Over 2 Amps Package - Stries G7J Relay Type General Purpose Coil Current 167mA Coil Current 167mA Coil Voltage 12VDC Contact Form 4PST (3 Form A, 1 Form B) Contact Rating (Current) 25A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 50ms Release Time 50ms Features Test Button		
CategoryRelaysPower Relays, Over 2 AmpsPackagePackageSeriesG7JRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current167mACoil Voltage12VDCContact Form4PST (3 Form A, 1 Form B)Contact Rating (Current)25ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Man)9 VDCTurn On Voltage (Min)1.2 VDCOperate TimeSomsRelease TimeSomsFeaturesTest ButtonMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G7J-3A1B-PZ DC12
Power Relays, Over 2 AmpsPackage-SeriesG7JRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current167mACoil Voltage12VDCContact Form4PST (3 Form A, 1 Form B)Contact Rating (Current)25ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate TimeSomsRelease TimeSomsFeaturesTest ButtonMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Omron Automation and Safety
Package-SeriesG7JRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current167mACoil Voltage12VDCContact Form4PST (3 Form A, 1 Form B)Contact Rating (Current)25ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time50msRelease Time50msFeaturesTest ButtonMounting TypeChrief HoleTermination StylePC Pin	Category	Relays
SeriesG7JRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current167mACoil Voltage12VDCContact Form4PST (3 Form A, 1 Form B)Contact Rating (Current)25ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time50msRelease Time50msFeaturesTest ButtonMounting TypePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current167mACoil Voltage12VDCContact Form4PST (3 Form A, 1 Form B)Contact Rating (Current)25ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9 VDCOperate Time50msRelease Time50msFeaturesTest ButtonMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current167mACoil Voltage12VDCContact Form4PST (3 Form A, 1 Form B)Contact Rating (Current)25ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time50msRelease Time50msFeaturesTest ButtonMounting TypePC PinTermination StylePC Pin	Series	G7J
Coil Current167mACoil Voltage12VDCContact Form4PST (3 Form A, 1 Form B)Contact Rating (Current)25ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time50msRelease Time50msFeaturesTest ButtonMounting TypeThrough HolePC Pin1000000000000000000000000000000000000	Relay Type	General Purpose
Coil Voltage12VDCContact Form4PST (3 Form A, 1 Form B)Contact Rating (Current)25ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time50msRelease Times50msFeaturesTest ButtonMounting TypeThrough HolePermination StylePC Pin	Coil Type	Non Latching
Contact Form4PST (3 Form A, 1 Form B)Contact Rating (Current)25ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time50msRelease Time50msFeaturesTest ButtonMounting TypeThrough HolePC PinPC	Coil Current	167mA
Contact Rating (Current)25ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time50msRelease Time50msFeaturesTest ButtonMounting TypeThrough HolePermination StylePC Pin	Coil Voltage	12VDC
Switching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time50msRelease Time50msFeaturesTest ButtonMounting TypeThrough HoleTermination StylePC Pin	Contact Form	4PST (3 Form A, 1 Form B)
Turn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time50msRelease Time50msFeaturesTest ButtonMounting TypeThrough HoleFermination StylePC Pin	Contact Rating (Current)	25A
Turn Off Voltage (Min)1.2 VDCOperate Time50msRelease Time50msFeaturesTest ButtonMounting TypeThrough HoleTermination StylePC Pin	Switching Voltage	250VAC, 125VDC - Max
Operate Time50msRelease Time50msFeatures50msMounting TypeTest ButtonTermination StylePC Pin	Turn On Voltage (Max)	9 VDC
Release Time50msFeaturesTest ButtonMounting TypeThrough HoleTermination StylePC Pin	Turn Off Voltage (Min)	1.2 VDC
FeaturesTest ButtonMounting TypeThrough HoleTermination StylePC Pin	Operate Time	50ms
Mounting TypeThrough HoleTermination StylePC Pin	Release Time	50ms
Termination Style PC Pin	Features	Test Button
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

G7J-3A1B-PZ DC12 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

G7J-3A1B-PZ DC12 Payment Methods



G7J-3A1B-PZ DC12 Shipping Methods



If you have any question about G7J-3A1B-PZ DC12, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com