

G7L-1A-BUB DC100

G7L-1A-BUB DC100 Information

Heisener.com	 G7L-1A-BUB DC100 Omron Electronics Inc-EMC Div Relays Power Relays, Over 2 Amps RELAY GEN PURPOSE SPST 30A 100V - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G7L-1A-BUB DC100 Specifications

Manufacturer Part Number GTL-1A-BUB DC100 Manufacturer Omron Electronics Inc-EMC Div Category Relays Package Power Relays, Over 2 Amps Package - Series GTL Relay Type General Purpose Coil Type Non Latching Coil Current 19mA Coil Acting Current) SPST-NO (I Form A) Cotact Form SOVAC - Max Switching Voltage (Max) 5VDC Turn On Voltage (Max) 5VDC Operator Time Joms Release Time Joms Features - Features Chasis Mount Features Screw Terminal		
CategoryRelaysPackage-PackageGrace Relays, Over 2 AmpsPackage-SeriesGTLRelay TypeGeneral PurposeColl TypeNon LatchingColl Current19mAColl Current100 VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage250 VAC - MaxTurn ON Voltage (Max)5 VDCCurrent15 VDCOperate Time30msRelease Time-Features-Mounting TypeChasis MountFemination StyleScew Terminal	Manufacturer Part Number	G7L-1A-BUB DC100
PackagePower Relays, Over 2 AmpsPackage-SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current19mACoil Otage100VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage250VAC - MaxTurn On Voltage (Max)75 VDCOperate Time30msRelease Time30msFeatures-Mounting TypeChasis MountTermination StyleScrew Terminal	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current19mACoil Voltage100VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage250VAC - MaxTurn On Voltage (Max)75 VDCOperate Time30msRelease Time30msFeatures-Mounting TypeChasis MountTermination StyleScrew Terminal	Category	Relays
SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current19mACoil Voltage100 VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage250 VAC - MaxTurn On Voltage (Max)75 VDCTurn Off Voltage (Min)15 VDCOperate Time30msRelease Time-Mounting TypeChasis MountTermination StyleScrew Terminal		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current19mACoil Voltage100VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage250VAC - MaxTurn On Voltage (Max)75 VDCOperate Time30msRelase Time30msFeatures-Mounting TypeChasis MountTermination StyleScrew Terminal	Package	-
Coil TypeNon LatchingCoil Current19mACoil Voltage100VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage250VAC - MaxTurn On Voltage (Max)75 VDCOperate Time30msRelease Time30msFeatures-Mounting TypeChasis MountTermination StyleScrew Terminal	Series	G7L
Coil Current19mACoil Voltage100VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage250VAC - MaxTurn On Voltage (Max)75 VDCTurn Off Voltage (Min)15 VDCOperate Time30msRelease Time30msFeatures-Mounting TypeChassis MountTermination StyleScrew Terminal	Relay Type	General Purpose
Coil Voltage100VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage250VAC - MaxTurn On Voltage (Max)75 VDCTurn Off Voltage (Min)15 VDCOperate Time30msRelease Time30msFeatures-Mounting TypeChasis MountTermination StyleScrew Terminal	Coil Type	Non Latching
Contact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage250VAC - MaxTurn On Voltage (Max)75 VDCTurn Off Voltage (Min)15 VDCOperate Time30msRelease Time30msFeatures-Mounting TypeChassis MountTermination StyleScrew Terminal	Coil Current	19mA
Contact Rating (Current)30ASwitching Voltage250VAC - MaxTurn On Voltage (Max)75 VDCTurn Off Voltage (Min)15 VDCOperate Time30msRelease Time30msFeatures-Mounting TypeChassis MountTermination StyleScrew Terminal	Coil Voltage	100VDC
Switching Voltage250VAC - MaxTurn On Voltage (Max)75 VDCTurn Off Voltage (Min)15 VDCOperate Time30msRelease Time30msFeatures-Mounting TypeChassis MountTermination StyleScrew Terminal	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)75 VDCTurn Off Voltage (Min)15 VDCOperate Time30msRelease Time30msFeatures-Mounting TypeChassis MountTermination StyleScrew Terminal	Contact Rating (Current)	30A
Turn Off Voltage (Min)15 VDCOperate Time30msRelease Time30msFeatures-Mounting TypeChassis MountTermination StyleScrew Terminal	Switching Voltage	250VAC - Max
Operate Time30msRelease Time30msFeatures-Mounting TypeChassis MountTermination StyleScrew Terminal	Turn On Voltage (Max)	75 VDC
Release Time30msFeatures-Mounting TypeChassis MountTermination StyleScrew Terminal	Turn Off Voltage (Min)	15 VDC
Features-Mounting TypeChassis MountTermination StyleScrew Terminal	Operate Time	30ms
Mounting TypeChassis MountTermination StyleScrew Terminal	Release Time	30ms
Termination Style Screw Terminal	Features	-
· ·	Mounting Type	Chassis Mount
Report errors?	Termination Style	Screw Terminal
		Report errors?

G7L-1A-BUB DC100 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

G7L-1A-BUB DC100 Payment Methods





If you have any question about G7L-1A-BUB DC100, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com