

# G7L-1A-BUB-J-CB-AC24

### G7L-1A-BUB-J-CB-AC24 Information



For Reference Only

Part Number G7L-1A-BUB-J-CB-AC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPST 30A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **G7L-1A-BUB-J-CB-AC24 Specifications**

Manufacturer Part Number         G7L-1A-BUB-J-CB-AC24           Manufacturer         Omron Electronics Inc-EMC Div           Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         G7L           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         71mA           Coil Voltage         24VAC           Contact Form         SPST-NO (1 Form A)           Contact Rating (Current)         30A           Switching Voltage         250VAC - Max           Turn On Voltage (Max)         18 VAC           Turn Off Voltage (Min)         3.6 VAC           Operate Time         30ms           Release Time         30ms           Features         Insulation - Class B, Test Button           Mounting Type         Chassis Mount           Termination Style         Screw Terminal		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current71mACoil Voltage24VACContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage250VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)3.6 VACOperate Time30msRelease Time30msFeaturesInsulation - Class B, Test ButtonMounting TypeChassis MountTermination StyleScrew Terminal	Manufacturer Part Number	G7L-1A-BUB-J-CB-AC24
Package - Series G7L Relay Type General Purpose Coil Type Non Latching Coil Current 71mA Coil Voltage 24VAC Contact Form SPST-NO (1 Form A) Switching Voltage 250VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) Operate Time 30ms Release Time 30ms Features Insulation - Class B, Test Button Mounting Type Chassis Mount Termination Style Seneral Purpose Gnacl Garage Gar	Manufacturer	Omron Electronics Inc-EMC Div
Package         -           Series         G7L           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         71mA           Coil Voltage         24VAC           Contact Form         SPST-NO (1 Form A)           Contact Rating (Current)         30A           Switching Voltage         250VAC - Max           Turn On Voltage (Max)         18 VAC           Turn Off Voltage (Min)         3.6 VAC           Operate Time         30ms           Release Time         30ms           Features         Insulation - Class B, Test Button           Mounting Type         Chassis Mount           Termination Style         Screw Terminal	Category	Relays
SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current71mACoil Voltage24VACContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage250VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)3.6 VACOperate Time30msRelease Time30msFeaturesInsulation - Class B, Test ButtonMounting TypeChassis MountTermination StyleScrew Terminal		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 71mA Coil Voltage 24VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 250VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 30ms Release Time 30ms Release Time 100ms 100ms Features Insulation - Class B, Test Button Mounting Type Chassis Mount Termination Style Screw Terminal	Package	-
Coil TypeNon LatchingCoil Current71mACoil Voltage24VACContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage250VAC - MaxTurn On Voltage (Max)18 VACTurn Off Voltage (Min)3.6 VACOperate Time30msRelease Time30msFeaturesInsulation - Class B, Test ButtonMounting TypeChassis MountTermination StyleScrew Terminal	Series	G7L
Coil Current Coil Voltage 24VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 250VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 30ms Release Time 30ms Features Insulation - Class B, Test Button Mounting Type Chassis Mount Termination Style SPST-NO (1 Form A)  30A SPST-NO (1 Form A) 30A SPST-NO (1 Form A) 30A SPST-NO (1 Form A) 30A SPST-NO (1 Form A) 30A SPST-NO (1 Form A) 30A SPST-NO (1 Form A) 30A SPST-NO (1 Form A) 30A SPST-NO (1 Form A) SPST-NO (1 Form A) 30A SPST-NO (1 Form A) SPST-NO (	Relay Type	General Purpose
Coil Voltage 24VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 30A Switching Voltage 250VAC - Max Turn On Voltage (Max) 18 VAC Turn Off Voltage (Min) 3.6 VAC Operate Time 30ms Release Time 30ms Release Time Insulation - Class B, Test Button Mounting Type Chassis Mount Termination Style SPST-NO (1 Form A) SPST-NO (1 Form A) SPST-NO (1 Form A) SOA	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 30A  Switching Voltage 250VAC - Max  Turn On Voltage (Max) 18 VAC  Turn Off Voltage (Min) 3.6 VAC  Operate Time 30ms  Release Time 30ms  Release Time Insulation - Class B, Test Button  Mounting Type Chassis Mount  Termination Style Screw Terminal	Coil Current	71mA
Contact Rating (Current)  Switching Voltage  250VAC - Max  Turn On Voltage (Max)  18 VAC  Turn Off Voltage (Min)  3.6 VAC  Operate Time  30ms  Release Time  30ms  Features  Insulation - Class B, Test Button  Mounting Type  Chassis Mount  Termination Style  Screw Terminal	Coil Voltage	24VAC
Switching Voltage  Turn On Voltage (Max)  18 VAC  Turn Off Voltage (Min)  Operate Time  30ms  Release Time  30ms  Features  Insulation - Class B, Test Button  Mounting Type  Chassis Mount  Termination Style  Screw Terminal	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)  18 VAC  Turn Off Voltage (Min)  3.6 VAC  Operate Time  30ms  Release Time  30ms  Features  Insulation - Class B, Test Button  Mounting Type  Chassis Mount  Termination Style  Screw Terminal	Contact Rating (Current)	30A
Turn Off Voltage (Min)  Operate Time  30ms  Release Time  30ms  Features  Insulation - Class B, Test Button  Mounting Type  Chassis Mount  Termination Style  Screw Terminal	Switching Voltage	250VAC - Max
Operate Time 30ms  Release Time 30ms  Features Insulation - Class B, Test Button  Mounting Type Chassis Mount  Termination Style Screw Terminal	Turn On Voltage (Max)	18 VAC
Release Time 30ms Features Insulation - Class B, Test Button Mounting Type Chassis Mount Termination Style Screw Terminal	Turn Off Voltage (Min)	3.6 VAC
Features Insulation - Class B, Test Button  Mounting Type Chassis Mount  Termination Style Screw Terminal	Operate Time	30ms
Mounting Type Chassis Mount Termination Style Screw Terminal	Release Time	30ms
Termination Style Screw Terminal	Features	Insulation - Class B, Test Button
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Screw Terminal
		Report errors?

#### G7L-1A-BUB-J-CB-AC24 Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **G7L-1A-BUB-J-CB-AC24** Payment Methods



















### G7L-1A-BUB-J-CB-AC24 Shipping Methods













If you have any question about G7L-1A-BUB-J-CB-AC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com