

G7L-1A-BUB-J-CB-DC12 Information



Part Number	G7L-1A-BUB-J-CB-DC12
Manufacturer	Omron Electronics Inc-EMC Div
Category	Relays Power Relays, Over 2 Amps
Description	RELAY GEN PURPOSE SPST 30A 12V
Package	-
	For the pricing/inventory/lead time, please contact
	us
	Website: https://www.heisener.com
	E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G7L-1A-BUB-J-CB-DC12 Specifications

Manufacturer Part NumberG7L-1A-BUB-J-CB-DC12ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysPower Relays, Over 2 AmpsPower Relays, Over 2 AmpsPackage-SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current158mAContact FormSPST-NO (1 Form A)Contact Rating (Current)SPST-NO (1 Form A)Switching Voltage20VAC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.8 VDC
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current158mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage (Max)9 VDC
PackagePower Relays, Over 2 AmpsPackage-SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current158mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage250VAC - MaxTurn On Voltage (Max)9 VDC
Package-SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current158mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage250VAC - MaxFurn On Voltage (Max)9 VDC
SeriesG7LRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current158mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage250VAC - MaxTurn On Voltage (Max)9 VDC
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current158mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage250VAC - MaxTurn On Voltage (Max)9 VDC
Coil TypeNon LatchingCoil Current158mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage250VAC - MaxTurn On Voltage (Max)9 VDC
Coil Current158mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage250VAC - MaxTurn On Voltage (Max)9 VDC
Coil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage250VAC - MaxTurn On Voltage (Max)9 VDC
Contact FormSPST-NO (1 Form A)Contact Rating (Current)30ASwitching Voltage250VAC - MaxTurn On Voltage (Max)9 VDC
Contact Rating (Current)30ASwitching Voltage250VAC - MaxTurn On Voltage (Max)9 VDC
Switching Voltage250VAC - MaxTurn On Voltage (Max)9 VDC
Turn On Voltage (Max) 9 VDC
Turn Off Voltage (Min) 18 VDC
Operate Time 30ms
Release Time 30ms
Features Insulation - Class B, Test Button
Mounting Type Chassis Mount
Termination Style Screw Terminal
Report errors?

G7L-1A-BUB-J-CB-DC12 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

G7L-1A-BUB-J-CB-DC12 Payment Methods





If you have any question about G7L-1A-BUB-J-CB-DC12, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com